

Zebra LS2208 Lecteur de code barre portable 1D Laser Noir, Blanc

Marque : Zebra

Code produit: LS2208-7AZU0100ZNA

Nom du produit : LS2208

Zebra LS2208. Type: Lecteur de code barre portable, Type de scanner: 1D, Type de capteur: Laser. Technologie de connectivité: Avec fil, Interfaces standards: RS-232, RS-485, Décodeur d'interface clavier, USB. Couleur du produit: Noir, Blanc, Code (IP) Internationale Protection: IP30, Fonctions de protection: Résistant aux chutes, Résistant aux rayures. Type de source d'alimentation: CC, Tension d'entrée: 4.5 - 5.5 V, Consommation électrique: 175 mA. Poids: 150 g, Largeur: 64 mm, Profondeur: 85 mm



Numérisation		représentation / réalisation	
Type *	Lecteur de code barre portable	Certification	EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011 + AC 2011; IEC 60950-1: 2005 + A1: 2009; UL 60950-1, second edition; CAN/CSA-C22.2 No. 60950-1-07 FCC 47 CFR Part 15, Subpart B, Class B; ICES-003 Issue 4, Class B; Compliant with EMC Directive 2004/108/EC CDRH Class II; IEC Class 2
Type de scanner *	1D		
Type de capteur *	Laser		
Linéaires (1D) codes barres acceptés *	Codabar, Code 11, Code 128, Code 39 (ASCII), Code 93, GS1 DataBar, Pharmacode, Plessey, Standard 2 of 5		
Résolution du scanner	3 mm		
Distance de lecture	63,5 cm		
Taux de lecture (max)	100 lectures/seconde		
Niveaux de luminosité (rayon direct du soleil)	0 - 86080 lux		
Longueur d'onde	650 nm		
Angle de lecture: Inclinaison (Tilt)	-10 - 10°		
Angle de lecture Horizontal (Pitch)	-65 - 65°		
Angle de lecture Vertical (Yaw)	-60 - 60°		
Connectivité		Puissance	
Technologie de connectivité *	Avec fil	Type de source d'alimentation *	CC
Interfaces standards *	RS-232, RS-485, Décodeur d'interface clavier, USB	Tension d'entrée	4.5 - 5.5 V
		Consommation électrique	175 mA
		Poids et dimensions	
		Largeur	64 mm
		Profondeur	85 mm
		Hauteur	152 mm
		Poids *	150 g
		Informations sur l'emballage	
		Câbles inclus	USB
représentation / réalisation		Conditions environnementales	
Code (IP) Internationale Protection	IP30	Température d'opération	0 - 50 °C
Fonctions de protection	Résistant aux chutes, Résistant aux rayures	Température hors fonctionnement	-40 - 70 °C
Voyants	✓	Humidité relative de fonctionnement (H-H)	5 - 95%
Couleur du produit *	Noir, Blanc	Résistance aux chutes	0,5 m
		Technical details	
		Certificats de conformité	Federal Communications Commission (FCC), RoHS

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.