

StarTech.com N6PAT20BLS câble de réseau Bleu 6,1 m Cat6 U/UTP (UTP) Rond

Marque : StarTech.com

Code produit: N6PAT20BLS

Nom du produit : N6PAT20BLS

StarTech.com N6PAT20BLS. Longueur de câble: 6,1 m, Câble standard: Cat6, Blindage du câble: U/UTP (UTP), Connecteur 1: RJ-45, Connecteur 2: RJ-45, Contacts du connecteur de placage: Or, Taux de transfert de données: 1000 Mbit/s, Couleur du produit: Bleu



| Caractéristiques                                                |                                 | Caractéristiques                          |              |
|-----------------------------------------------------------------|---------------------------------|-------------------------------------------|--------------|
| Couleur du produit *                                            | Bleu                            | Budget Total Power over Ethernet (PoE)    | 90 W         |
| Longueur de câble *                                             | 6,1 m                           | Câble avec protection anticoupure         | ✓            |
| Câble standard *                                                | Cat6                            | Plug and Play                             | ✓            |
| Blindage du câble *                                             | U/UTP (UTP)                     | Conditions environnementales              |              |
| Connecteur 1 *                                                  | RJ-45                           | Température d'opération                   | 10 - 60 °C   |
| Connecteur 2 *                                                  | RJ-45                           | Température hors fonctionnement           | -20 - 60 °C  |
| Genre de connecteur 1 *                                         | Mâle                            | Humidité relative de fonctionnement (H-H) | 10 - 80%     |
| Genre de connecteur 2 *                                         | Mâle                            | Certificat                                |              |
| Facteur de forme du connecteur 1                                | Droit                           | Certificats de conformité                 | CE, RoHS     |
| Facteur de forme du connecteur 2                                | Droit                           | Poids et dimensions                       |              |
| Contacts du connecteur de placage                               | Or                              | Diamètre extérieur                        | 3,6 mm       |
| Matériau du manteau                                             | LSZH (Low smoke zero halogen )  | Contenu de l'emballage                    |              |
| Forme du câble *                                                | Rond                            | Quantité                                  | 1 pièce(s)   |
| Type de conducteur                                              | Gainé                           | Informations sur l'emballage              |              |
| Matériau conducteur                                             | Cuivre                          | Largeur du colis                          | 220 mm       |
| Technologie de câblage                                          | 10/100/1000Base-T(X)            | Profondeur du colis                       | 200 mm       |
| Type d'interface Ethernet                                       | Fast Ethernet, Gigabit Ethernet | Hauteur du colis                          | 10 mm        |
| Standards réseau                                                | IEEE 802.3bt                    | Poids du paquet                           | 121,2 g      |
| Taille des fils AWG                                             | 28                              | Données logistiques                       |              |
| Taux de transfert de données                                    | 1000 Mbit/s                     | Largeur du carton principal               | 420 mm       |
| Fréquence                                                       | 250 MHz                         | Longueur du carton principal              | 420 mm       |
| Connexion Ethernet, supportant l'alimentation via ce port (PoE) | ✓                               | Hauteur du carton principal               | 250 mm       |
| Type Power over Ethernet (PoE) pris en charge                   | PoE++ (4PPoE)                   | Quantité par carton principal             | 120 pièce(s) |



0065030915243



065030915243

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.