# Zebra ZT231 imprimante pour étiquettes Transfert thermique 203 x 203 DPI 305 mm/sec Avec fil &sans fil Ethernet/LAN Bluetooth

**Marque :** Zebra

**Code produit:** ZT23142-T0100AFZ

**Nom du produit :** ZT231

Zebra ZT231. Technologie d'impression: Transfert thermique, Résolution maximale: 203 x 203 DPI, Vitesse d'impression (mesure métrique): 305 mm/sec. Technologie de connectivité: Avec fil &sans fil, Ethernet/LAN, Bluetooth. Couleur du produit: Noir

| Vitesse d'impression | |
|---|---|
| Technologie d'impression * | Transfert thermique |
| Couleur * | ✗ |
| Résolution maximale * | 203 x 203 DPI |
| Vitesse d'impression (mesure métrique) * | 305 mm/sec |
| Largeur maximum d'impression * | 10,4 cm |

| Gestion du papier | |
|---|---|
| Largeur du ruban | 11 cm |
| Longueur de ruban | 450 m |
| Épaisseur du support | 0.076 - 0.010 mm |
| Longueur max. du support | 3,99 m |
| Diamètre principal | 2,54 cm |

| Connectivité | |
|---|---|
| Technologie de connectivité * | Avec fil &sans fil |
| Ethernet/LAN * | ✓ |
| Wifi * | ✗ |
| Bluetooth | ✓ |
| Bluetooth Low Energy (BLE) | ✓ |
| Port USB * | ✗ |
| Port RS-232 | 1 |
| Hôte USB | ✓ |

| représentation / réalisation | |
|---|---|
| Langues de la description de page | EPL, EPL2, ZBI, ZPL, ZPL II |
| Mémoire interne | 256 Mo |
| Mémoire flash | 256 Mo |

| Design | |
|---|---|
| Couleur du produit * | Noir |

| Design | |
|---|---|
| Écran integré | ✓ |
| Écran * | LCD |
| Taille de l'écran | 10,9 cm (4.3") |
| Affichage couleur | ✓ |
| Type de commande | Tactile |

| Puissance | |
|---|---|
| Tension d'entrée AC | 100-240 V |
| Fréquence d'entrée AC | 50-60 Hz |

| Configuration minimale du système | |
|---|---|
| Prise en charge du système d'exploitation Windows | ✓ |
| Prise en charge du système d'exploitation Mac | ✓ |
| Système mobile supporté | Android, iOS |

| Conditions environnementales | |
|---|---|
| Humidité relative de fonctionnement (H-H) | 20 - 85% |
| Taux d'humidité relative (stockage) | 5 - 85% |
| Température d'opération | 5 - 40 °C |
| Température hors fonctionnement | -40 - 60 °C |

| Poids et dimensions | |
|---|---|
| Largeur | 241 mm |
| Profondeur | 432 mm |
| Hauteur | 279 mm |
| Poids | 9,1 kg |

| Données logistiques | |
|---|---|
| Code du système harmonisé | 84433210 |

**Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 25-OCT-2026. Prints or copies of Information are only valid on the printed Publication date