

TP-Link Omada ER8411 Routeur connecté Gigabit Ethernet Noir

Marque : TP-Link

Famille de produit: Omada

Code produit: ER8411

Nom du produit : ER8411

TP-Link Omada ER8411. Standards réseau: IEEE 802.1Q, Type d'interface Ethernet: Gigabit Ethernet, Technologie de câblage: 10/100/1000Base-T(X). Fonction NAT: One-to-One NAT; Multi-Net NAT; Virtual Server; Port Triggering; NAT-DMZ; FTP/H.323/SIP/IPSec/PPTP.... Mémoire flash: 256 Mo, Mémoire interne: 4096 Mo, Type de mémoire interne: DDR4. Couleur du produit: Noir. Tension d'entrée AC: 100 - 240 V, Fréquence d'entrée AC: 50 - 60 Hz



Connexion WAN		Sécurité	
Ethernet WAN *	✓	Fonction NAT	One-to-One NAT; Multi-Net NAT; Virtual Server; Port Triggering; NAT-DMZ; FTP/H.323/SIP/IPSec/PPTP ALG; UPnP;
DSL WAN *	✗		
Emplacement de carte SIM *	✗		
Compatibilité modem USB 3G/4G *	✗		
WAN SFP *	✓		
Réseau		Contenu de l'emballage	
Standards réseau *	IEEE 802.1Q	Adaptateur secteur fourni	✓
Type d'interface Ethernet *	Gigabit Ethernet	Manuel d'utilisation	✓
Technologie de câblage	10/100/1000Base-T(X)	Caractéristiques	
LAN Ethernet : taux de transfert des données	10,100,1000 Mbit/s	Intégré dans le processeur	✓
Route statique	✓	Mémoire flash	256 Mo
Support VLAN	✓	Mémoire interne	4096 Mo
Redirection de port	✓	Type de mémoire interne	DDR4
Caractéristiques de gestion		Certification	CE, FCC, RoHS
Reconnaissance automatique des composants de l'ordinateur	✓	Design	
Bouton de réinitialisation	✓	Couleur du produit *	Noir
Connectivité		Voyants	✓
Nombre de port ethernet LAN (RJ-45) *	8	Puissance	
Quantité de ports Combo SFP	2	Tension d'entrée AC	100 - 240 V
Nombre de ports USB	2	Fréquence d'entrée AC	50 - 60 Hz
Entrée DC	✓	Conditions environnementales	
Protocoles		Température d'opération	0 - 40 °C
Client DHCP *	✓	Température hors fonctionnement	-40 - 70 °C
		Humidité relative de fonctionnement (H-H)	10 - 90%
		Taux d'humidité relative (stockage)	5 - 90%
		Poids et dimensions	

Protocoles		Poids et dimensions	
Serveur DHCP *	✓	Largeur	440 mm
Sécurité		Profondeur	220 mm
Filtrage URL	✓	Hauteur	44 mm
Liste de contrôle d'accès (ACL)	✓	Informations sur l'emballage	
		Largeur du colis	336 mm
		Profondeur du colis	528 mm
		Hauteur du colis	100 mm
		Poids du paquet	3,68 kg



4897098683309



4897098683132



0840030703300



840030703300

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.