

TP-Link Omada ES206X-M2 commutateur réseau Géré L2 2.5G Ethernet (100/1000/2500) Montage sur le bureau ou sur le mur Noir



Marque : TP-Link

Famille de produit: Omada

Code produit: ES206X-M2

Nom du produit : ES206X-M2

TP-Link Omada ES206X-M2. Type de commutateur: Géré, Banc de commutateurs: L2. Type de port Ethernet RJ-45 de commutation de base: 2.5G Ethernet (100/1000/2500), Quantité de ports Ethernet RJ-45 de commutation de base: 5. Répertoire MAC: 16000 entrées, Capacité de commutation: 45 Gbit/s. Standards réseau: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3z, IEEE 802.3ae, IEEE 802.3aq, IEEE.... Format: Montage sur le bureau ou sur le mur

Caractéristiques de gestion		Sécurité	
Type de commutateur *	Géré	Filtrage IGMP	✓
Banc de commutateurs	L2	Design	
Qualité de service (QoS)	✓	Format	Montage sur le bureau ou sur le mur
Connectivité		Couleur du produit	Noir
Quantité de ports Ethernet RJ-45 de commutation de base *	5	Voyants	✓
Type de port Ethernet RJ-45 de commutation de base *	2.5G Ethernet (100/1000/2500)	représentation / réalisation	
Quantités d'emplacements de module SFP+	1	Mémoire flash	64 Mo
Réseau		Micrologiciel évolutif	✓
Standards réseau *	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3z, IEEE 802.3ae, IEEE 802.3aq, IEEE 802.3x, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1ab	Temps moyen entre pannes	1223587 h
		Puissance	
Soutien 10G *	✗	Source d'alimentation *	Secteur
Port mirroring (Mise en miroir des ports)	✓	Tension d'entrée AC	100 - 240 V
Assistance contrôle des flux	✓	Consommation (max)	5,63 W
Agrégation de lien	✓	PoE (alimentation via le port Ethernet)	
Contrôle Broadcast storm	✓	Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✗
Support VLAN	✓	Conditions environnementales	
Fonctions LAN virtuelles	MTU VLAN, Port-based VLAN	Température d'opération	-5 - 40 °C
Transmission des données		Température hors fonctionnement	-40 - 70 °C
Capacité de commutation *	45 Gbit/s	Humidité relative de fonctionnement (H-H)	10 - 90%
Taux de transfert	33,48 Mpps	Taux d'humidité relative (stockage)	5 - 90%
Répertoire MAC *	16000 entrées	Dissipation thermique	19,21 BTU/h
Enregistrement-et-réémission	✓	Poids et dimensions	
Support de trames étendues (Jumbo Frames)	✓	Largeur	158 mm
Trames géantes	10	Profondeur	100,7 mm
Mémoire cache de paquet	0,64 Mo	Hauteur	25,4 mm
Sécurité		Poids	520 g
Fonctions DHCP	DHCP client	Certificat	
		Certification	CE, FCC, RoHS



1210002600729



0840460600323



840460600323

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.