



TP-Link Omada IES206G commutateur réseau Géré Gigabit Ethernet (10/100/1000) Noir

Marque : TP-Link

Famille de produit: Omada

Code produit: IES206G

Nom du produit : IES206G

TP-Link Omada IES206G. Type de commutateur: Géré. Type de port Ethernet RJ-45 de commutation de base: Gigabit Ethernet (10/100/1000), Quantité de ports Ethernet RJ-45 de commutation de base: 4. Répertoire MAC: 8000 entrées, Capacité de commutation: 12 Gbit/s. Standards réseau: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Voltage d'entrée DC: 9 - 60 V. Montage mural

Caractéristiques de gestion		Sécurité	
Type de commutateur *	Géré	Fonctions DHCP	DHCP client
Qualité de service (QoS)	✓	Filtrage IGMP	✓
Gestion basée sur le web	✓	Caractéristiques de multidiffusion	
Géré sur le Cloud	✓	Support à la multidifusion	✓
Connectivité		Design	
Quantité de ports Ethernet RJ-45 de commutation de base *	4	Couleur du produit	Noir
Type de port Ethernet RJ-45 de commutation de base *	Gigabit Ethernet (10/100/1000)	Montage mural	✓
Quantité de ports Combo SFP	1	Montage des rails DIN	✓
Quantité d'emplacements de modules SFP	1	représentation / réalisation	
Réseau		Puissance	
Standards réseau *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Source d'alimentation *	CC
Soutien 10G *	✗	Bloc d'alimentation inclus *	✓
Port mirroring (Mise en miroir des ports)	✓	Alimentation redondante (RPS)	✓
Assistance contrôle des flux	✓	Voltage d'entrée DC	9 - 60 V
Agrégation de lien	✓	PoE (alimentation via le port Ethernet)	
Auto MDI/MDI-X	✓	Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✗
Protocles Spanning Tree (STP)	✓	Conditions environnementales	
Négociation automatique	✓	Température d'opération	-40 - 75 °C
Transmission des données		Température hors fonctionnement	-40 - 85 °C
Capacité de commutation *	12 Gbit/s	Humidité relative de fonctionnement (H-H)	5 - 95%
Taux de transfert	8,93 Mpps	Taux d'humidité relative (stockage)	5 - 95%
Répertoire MAC *	8000 entrées	Poids et dimensions	
Enregistrement-et-réémission	✓	Largeur	129 mm
Support de trames étendues (Jumbo Frames)	✓	Profondeur	95 mm
Trames géantes	15000	Hauteur	45 mm
		Certificat	
		Certification	FCC, CE, RoHS



1210002602075



0840460600934



840460600934

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.