



TP-Link TL-SG1005P-PD commutateur réseau Gigabit Ethernet (10/100/1000) Connexion Ethernet, supportant l'alimentation via ce port (PoE) Noir

Marque : TP-Link

Code produit: TL-SG1005P-PD

Nom du produit : TL-SG1005P-PD

TP-Link TL-SG1005P-PD. Type de port Ethernet RJ-45 de commutation de base: Gigabit Ethernet (10/100/1000), Quantité de ports Ethernet RJ-45 de commutation de base: 5. Répertoire MAC: 2000 entrées, Capacité de commutation: 10 Gbit/s. Standards réseau: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3u,.... Connexion Ethernet, supportant l'alimentation via ce port (PoE). Montage mural



| Caractéristiques de gestion                               |                                                                                                            | représentation / réalisation                                      |               |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------|
| Qualité de service (QoS)                                  | ✓                                                                                                          | Sans ventilateur                                                  | ✓             |
| Connectivité                                              |                                                                                                            | Puissance                                                         |               |
| Quantité de ports Ethernet RJ-45 de commutation de base * | 5                                                                                                          | Source d'alimentation *                                           | PoE           |
| Type de port Ethernet RJ-45 de commutation de base *      | Gigabit Ethernet (10/100/1000)                                                                             | Bloc d'alimentation inclus *                                      | ✗             |
|                                                           |                                                                                                            | Consommation (max)                                                | 68,59 W       |
| Réseau                                                    |                                                                                                            | PoE (alimentation via le port Ethernet)                           |               |
| Standards réseau *                                        | IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x | Connexion Ethernet, supportant l'alimentation via ce port (PoE) * | ✓             |
| Soutien 10G *                                             | ✓                                                                                                          | Power over Ethernet (PoE) Nombre de ports                         | 5             |
| Technologie de câblage Ethernet cuivre                    | 10BASE-T, 100BASE-TX, 1000BASE-T                                                                           | Budget Total Power over Ethernet (PoE)                            | 66 W          |
| Types de câbles soutenus                                  | Cat3, Cat4, Cat5, Cat5e, Cat6                                                                              | Conditions environnementales                                      |               |
| Assistance contrôle des flux                              | ✓                                                                                                          | Température d'opération                                           | -30 - 70 °C   |
| Auto MDI/MDI-X                                            | ✓                                                                                                          | Température hors fonctionnement                                   | -40 - 70 °C   |
| Négociation automatique                                   | ✓                                                                                                          | Humidité relative de fonctionnement (H-H)                         | 10 - 90%      |
| Apprentissage automatique d'adresse MAC pris en charge    | ✓                                                                                                          | Taux d'humidité relative (stockage)                               | 5 - 90%       |
| Mise à jour automatique de l'adresse MAC                  | ✓                                                                                                          | Dissipation thermique                                             | 233,206 BTU/h |
| Transmission des données                                  |                                                                                                            | Poids et dimensions                                               |               |
| Capacité de commutation *                                 | 10 Gbit/s                                                                                                  | Largeur                                                           | 158 mm        |
| Taux de transfert                                         | 7,44 Mpps                                                                                                  | Profondeur                                                        | 101 mm        |
| Répertoire MAC *                                          | 2000 entrées                                                                                               | Hauteur                                                           | 25 mm         |
| Enregistrement-et-réémission                              | ✓                                                                                                          | Contenu de l'emballage                                            |               |
|                                                           |                                                                                                            | Guide d'utilisation                                               | ✓             |
|                                                           |                                                                                                            | Informations sur l'emballage                                      |               |
|                                                           |                                                                                                            | Type d'emballage                                                  | Boîte         |

| Sécurité               |                  | Certificat    |               |
|------------------------|------------------|---------------|---------------|
| Filtrage IGMP          | ✓                | Certification | CE, FCC, RoHS |
| Design                 |                  |               |               |
| Couleur du produit     | Noir             |               |               |
| Voyants                | ✓                |               |               |
| Montage mural          | ✓                |               |               |
| Nombre de ventilateurs | 0 ventilateur(s) |               |               |



4895252501117



4895252501124



0840030705700



840030705700

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.