USB C Video Adapter, USB C to HDMI DVI VGA Adapter, Up to 4K 60Hz, Aluminum, Multiport Video Display Adapter, Thunderbolt 3 / 4 Compatible, USB Type C Travel Adapter

Product ID: 118-USBC-HDMI-VGADVI



This USB-C multiport video adapter offers a durable and portable solution for connecting your USB Type-C device to a n HDMI, DVI, or VGA display.

The HDMI 2.0b output supports up to 4K 60 Hz resolutions and HDR whereas VGA output supports up to 1920x1200 at 60 Hz, and the DVI-I output supports up to 1080p at 60 Hz. All the outputs offer compatibility with older displays supporting lower resolution. The adapter supports dual mirrored 1080p displays when using either VGA and HDMI or VGA and DVI-I monitor configurations.

Avoid the hassle of carrying different adapters with a USB Type-C Multiport Video Adapter. Connect a USB-C DisplayPort Alt-mode device to virtually any display. A durable aluminum enclosure helps the adapter withstand being carried in a travel bag between office, home, shared spaces, and during business travel.

The USB Type-C Display Adapter is compatible with USB-C DisplayPort Alt-mode, Thunderbolt 3, Thunderbolt 4 Laptops, Ultrabooks, Chromebooks, and MacBooks. Plug and Play (PnP) capability allows you to quickly connect to devices running Windows, macOS, iPadOS, chromeOS, or Linux. The VGA and DVI outputs are compatible with screw locking cables ensuring a secure connection with displays and projectors. The 12 inch (30 cm) attached cable allows for flexibility in your setup and less strain on ports and connectors.

118-USBC-HDMI-VGADVI is backed for 3-years by StarTech.com, including free 24/5 multi-lingual technical assistance.

Certifications, Reports and Compatibility

Operating System Independent

Applications

• Carry the adapter with you when you travel, and connect to almost any display

• Connect your USB-C device to an HDMI, VGA, or DVI display at an office, home office, in shared spaces, or during business travel

• Connect a secondary VGA, DVI, or HDMI monitor to your MacBook

Features

• USB-C SINGLE MONITOR ADAPTER: USB-C DP Alt-mode to HDMI 2.0b (4K 60Hz, 7.1ch Audio, HDR, HDCP 2.2), VGA (1920x1200 60Hz) or DVI-I (1080p 60Hz, HDCP 1.4); This USB C to HDMI DVI VGA Adapter supports dual mirrored video output for VGA & HDMI or VGA & DVI-I

• 4K 60Hz RESOLUTION: The USB C Video Adapter's HDMI output supports 4K 60Hz and Ultra Wide Screen resolutions up to 3840x1080p 60Hz; Compatible with lower resolutions; Works with monitors and displays from Dell, Asus, Acer, LG, Samsung, Sharp, Sony

• WIDE HOST COMPATIBILITY: Compatible with USB-C, Thunderbolt 3 and Thunderbolt 4 Laptops, Ultrabooks and Chromebooks, from HP, Dell, Surface, Lenovo, MacBooks (Intel and M1 chip) The USB C Multiport Video Adapter works on Windows, macOS and Linux

• TOUGH & PORTABLE: Durable all aluminium USB Type-C multiport adapter with small form factor is designed for easy transport in a laptop bag; The USB C Video Adapter is convenient for on-the-go use between office, home, shared spaces, and business travel

• EASY TO USE: Plug and Play (PnP) installation, no software or drivers required; Extended 12" (30cm) attached cable for setup flexibility; The USB C Adapter is compatible with screw locking cables for secure connection with VGA/DVI displays and projectors

General		
	UPC	065030895583
	Package Quantity	1
	Warranty	3 Years
Special Notes / Requirements		
	Special Notes	This adapter does not support MST or dual extended displays
		Support for dual mirrored displays only using combinations of VGA & HDMI or VGA & DVI-I

Power

Power Source	Bus Powered
Power Delivery	No PD Pass-Through
Input Voltage	5V DC
Output Voltage	5 DC

Physical & Environmental

Color	Gray
Cable Length	11.8 in [30 cm]
Product Length	3.3 in [85.0 mm]
Product Width	1.8 in [45.0 mm]
Product Height	0.6 in [14.0 mm]
Weight of Product	2.6 oz [75.0 g]
Operating Temperature	0 to 45 (32F to 113F)
Storage Temperature	-10 to 70 (14F to 158F)
Humidity	10% ~ 85 % RH

Performance

HDR Support	Yes
Audio Specifications	VGA - No Audio Support
	DVI - No Audio Support
	HDMI - 7.1 Channel Audio
Maximum Analog Resolutions	1920 x 1200 @ 60 Hz (VGA)
Maximum Digital Resolutions	3840 x 2160 @ 60 Hz (HDMI)
	1920 x 1200 @ 60 Hz (DVI)
Wide Screen Supported	Yes

Hardware

Active or Passive Adapter	Active

	AV Input	USB-C
	AV Output	VGA
		DVI-I (Digital Only) - Dual-Link
		HDMI
	Number of Displays	1
	Chipset ID	ITE - IT6224FN
Packaging & In-the-Box		
	Included in Package	1 - USB-C Multiport Video Adapter
	Package Width	5.7 in [14.5 cm]
	Package Depth	6.8 in [17.3 cm]
	Package Height	1.3 in [33 mm]
	Shipping (Package) Weight	4.3 oz [122 g]
Connector(s)		
	Connector 1 (Quantity)	1
	Connector 1	USB-C DP++ (DP Alt-Mode)
	Connector 2 (Quantity)	1
	Connector 2	VGA
	Connector 3 (Quantity)	1
	Connector 3	DVI-I Dual-Link (29-Pin)
	Connector 4 (Quantity)	1
	Connector 4	HDMI

Product appearance and specifications are subject to change without notice.