Canon

Canon imageFORMULA CR-L1 300 x 300 DPI Noir, Gris



Marque : Canon

Famille de produit: imageFORMULA

Code produit: 3595C002

Nom du produit : CR-L1



Canon imageFORMULA CR-L1. Surface maximal de numérisation: 108 x 228 mm, Résolution de numérisation optique: 300 x 300 DPI, Profondeur d'affichage de sortie de couleur: 24 bit. Couleur du produit: Noir, Gris. Type de capteur: CMOS CIS, Cycle de fonctionnement par jour (max): 3000 pages, Source lumineuse: LED RGB. Capacité du chargeur automatique de documents: 50 feuilles. Épaisseur de supports (min): 0,08 mm, Épaisseur de la carte (max): 0,2 mm, Grammage du support, chargeur automatique de documents: 64 - 157 g/m²

Numérisation	
Surface maximal de numérisation *	108 x 228 mm
Résolution de numérisation optique *	300 x 300 DPI
Numérisation couleur	✔
Numérisation recto verso *	✔
Profondeur d'affichage de sortie de couleur	24 bit
Niveaux de gris	256

Design	
Couleur du produit *	Noir, Gris
Écran integré *	✘

représentation / réalisation	
Type de capteur *	CMOS CIS
Source lumineuse	LED RGB
Cycle de fonctionnement par jour (max) *	3000 pages

Capacité d'entrée	
Capacité du chargeur automatique de documents	50 feuilles

Gestion du papier	
Mode papier long	✔
Épaisseur de supports (min)	0,08 mm
Épaisseur de la carte (max)	0,2 mm
Grammage du support, chargeur automatique de documents	64 - 157 g/m²

Connectivité	
Port USB *	✔
Version USB	2.0
Interfaces standards	USB 2.0

Puissance	
Consommation électrique typique	15,8 W
Fréquence d'entrée AC	50 - 60 Hz
Tension d'entrée	220-240 V
Consommation d 'énergie (en mode veille)	2,3 W

Poids et dimensions	
Largeur	140 mm
Profondeur	223 mm
Hauteur	188 mm
Poids	2,1 kg

Contenu de l'emballage	
Logiciels fournis	Ranger driver + IQA, Canon Scanning Utility

Configuration minimale du système	
Prise en charge du système d'exploitation Windows	Windows 10, Windows 7, Windows 8.1
Prise en charge du système d'exploitation serveur	Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016

Conditions environnementales	
Température d'opération	10 - 32,5 °C
Humidité relative de fonctionnement (H-H)	20 - 80%

0013803315158

013803315158

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date