Kensington

Kensington SD4750P Avec fil USB 3.2 Gen 2 (3.1 Gen 2) Type-C Noir

Marque : Kensington

Code produit: K39105NA

Nom du produit : SD4750P



Kensington SD4750P. Technologie de connectivité: Avec fil, Interface de l'hôte: USB 3.2 Gen 2 (3.1 Gen 2) Type-C, Délivrance de la puissance USB jusqu'à: 85 W. LAN Ethernet : taux de transfert des données: 100,10,1000 Mbit/s. Couleur du produit: Noir, Taux de transfert des données: 5 Gbit/s, Type HD: 4K Ultra HD. Type de source d'alimentation: CC. Prise en charge d'autres systèmes d'exploitation: ChromeOS



Connectivité	
Technologie de connectivité *	Avec fil
Interface de l'hôte *	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
Quantité de ports de type A USB 3.2 Gen 1 (3.1 Gen 1) *	5
Quantité de ports de type C USB 3.2 Gen 1 (3.1 Gen 1)	1
Capacité de puissance USB	✔
Révision de la délivrance de la puissance USB	3.0
Délivrance de la puissance USB jusqu'à	85 W
Quantité de ports HDMI *	2
Version HDMI	2.0
Quantité d'interface DisplayPorts	1
Version de DisplayPort	1.2
Entrée jack microphone *	✔
Sortie de casque *	1
Casque connection	3,5 mm
Entrée DC	✔

Réseau	
Ethernet/LAN *	✔
Nombre de port ethernet LAN (RJ-45)	1
LAN Ethernet : taux de transfert des données	100,10,1000 Mbit/s

représentation / réalisation	
Lecteur de cartes mémoires intégré *	✘
Taux de transfert des données	5 Gbit/s

représentation / réalisation	
Type HD	4K Ultra HD
Résolution (numérique maximum)	3840 x 2160 pixels
Nombre d'affichages pris en charge	2
Port de câble antivol	✔
Type d'emplacement de verrouillage de câble	Kensington
Couleur du produit *	Noir
Plug and Play	✔
Pays d'origine	Taïwan
Certification	TAA

Puissance	
Type de source d'alimentation	CC

Logiciel	
Prise en charge du système d'exploitation Windows	✔
Prise en charge du système d'exploitation Mac	✔
Prise en charge d'autres systèmes d'exploitation	ChromeOS

Poids et dimensions	
Largeur	273,1 mm
Profondeur	87,9 mm
Hauteur	117,1 mm

Informations sur l'emballage	
Poids du paquet	1,21 kg

Autres caractéristiques	
Systèmes d'exploitation compatibles	Chrome OS 44 or above; macOS 10.14 or above; Windows 7 or above
Nombre de ports USB	6

0085896391050

085896391050

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date