# StarTech.com 3F-MDP-HDMI2-4K60 câble vidéo et adaptateur 0,9 m Mini DisplayPort HDMI Type A (Standard) Noir






**Marque :** StarTech.com

**Code produit:** 3F-MDP-HDMI2-4K60

**Nom du produit :** 3F-MDP-HDMI2-4K60

StarTech.com 3F-MDP-HDMI2-4K60. Longueur de câble: 0,9 m, Connecteur 1: Mini DisplayPort, Connecteur 2: HDMI Type A (Standard). Compliance certificates: RoHS. Diamètre du câble: 5 mm. Largeur du colis: 220 mm, Profondeur du colis: 128 mm, Hauteur du colis: 15 mm. Quantité: 1 pièce(s)

| Caractéristiques | |
|---|---|
| Facteur de forme du connecteur 1 | Droit |
| Facteur de forme du connecteur 2 | Droit |
| Contacts du connecteur de placage | Or |
| Longueur de câble * | 0,9 m |
| Connecteur 1 * | Mini DisplayPort |
| Connecteur 2 * | HDMI Type A (Standard) |
| Genre de connecteur 1 * | Mâle |
| Genre de connecteur 2 * | Mâle |
| Version HDMI | 2.0 |
| HDCP | ✔ |
| Version de DisplayPort | 1.4 |
| Résolution maximale | 3840 x 2160 pixels |
| Résolutions graphiques prises en charge | 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2048 x 1536 (QXGA), 2560 x 1440, 3072 x 1728, 3200 x 1800, 3840 x 2160 |
| Bande passante | 32000 Mo/s |
| Couleur du produit | Noir |
| Jeu de composants | Parade PS176 |
| Matériau du manteau | Élastomère thermoplastique (TPE) |
| Matériau du boîtier du connecteur | Acrylonitrile-Butadiène-Styrène (ABS) |

| Caractéristiques | |
|---|---|
| Canaux audio pris en charge | 7.1 |
| Plug and Play | ✔ |
| **Conditions environnementales** | |
| Température d'opération | 0 - 40 °C |
| Température hors fonctionnement | -10 - 70 °C |
| **Certificat** | |
| Certificats de conformité | RoHS |
| **Poids et dimensions** | |
| Diamètre du câble | 5 mm |
| **Informations sur l'emballage** | |
| Largeur du colis | 220 mm |
| Profondeur du colis | 128 mm |
| Hauteur du colis | 15 mm |
| Poids du paquet | 32 g |
| **Contenu de l'emballage** | |
| Quantité | 1 pièce(s) |
| **Données logistiques** | |
| Largeur du carton principal | 530 mm |
| Longueur du carton principal | 320 mm |
| Hauteur du carton principal | 210 mm |
| Quantité par carton principal | 140 pièce(s) |



0065030926485



065030926485

**Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date