Eaton 5P3000RT alimentation d'énergie non interruptible 3 kVA 2700 W 7 sortie(s) CA



Marque : Eaton

Code produit: 5P3000RT

Nom du produit : 5P3000RT

Eaton 5P3000RT. capacité de la puissance de sortie: 3 kVA, Puissance de sortie: 2700 W, Tension de voltage à l'entrée (min): 89 V. Types de sortie AC: NEMA 5–20R, NEMA L5-30R, Prise mâle: NEMA L5-30P, Nombre de prises en sortie: 7 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Capacité de la batterie: 9 Ah, Tension des piles: 12 V. Format: Rack/Tour, Couleur du produit: Noir, Capacité du rack: 2U. Certification: FCC Part 15 subpart B Class A

Caractéristiques	
capacité de la puissance de sortie *	3 kVA
Puissance de sortie *	2700 W
Tension de voltage à l'entrée (min) *	89 V
Tension de voltage à l'entrée (max) *	151 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	102 V
Tension de voltage à la sortie (max)	132 V
Efficacité	99%
Facteur de puissance d'entrée	0,9
Niveau sonore	50 dB

Connectivité	
Types de sortie AC	NEMA 5–20R, NEMA L5-30R
Prise mâle	NEMA L5-30P
Nombre de prises en sortie	7 sortie(s) CA
Quantité de Ports USB 2.0	1
Port RS-232	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Capacité de la batterie	9 Ah
Tension des piles	12 V
Temps de secours type au chargement complet	4 min

Batterie	
Temps de secours type à demi de charge	10 min
Batterie échangeable à chaud	✔

Design	
Format *	Rack/Tour
Capacité du rack	2U
Longueur de câble	3 m
Couleur du produit *	Noir
Type d'écran	LCD
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 50 °C
Humidité relative de fonctionnement (H-H)	20 - 95%
Altitude de fonctionnement	0 - 3000 m

Certificat	
Certification	FCC Part 15 subpart B Class A

Safety regulation & standards	
Sécurité	UL1778; UL497A; cUL

Sustainability	
Certificats de durabilité	ENERGY STAR

Poids et dimensions	
Largeur	441 mm
Profondeur	647 mm
Hauteur	86 mm
Poids	40 kg

Autres caractéristiques	
Connexions sortie électrique	1 x L5-30R & 6 x NEMA 5-20R

0743172039668

743172039668

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date