Eaton 5P Rackmount alimentation d'énergie non interruptible 0,55 kVA 420 W 5 sortie(s) CA



Marque : Eaton

Code produit: 5P550R

Nom du produit : 5P Rackmount

Eaton 5P Rackmount. capacité de la puissance de sortie: 0,55 kVA, Puissance de sortie: 420 W, Tension de voltage à l'entrée (min): 89 V. Types de sortie AC: NEMA 5–15R, Prise mâle: NEMA 5-15P, Nombre de prises en sortie: 5 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Temps de secours type au chargement complet: 3 min, Temps de secours type à demi de charge: 8 min. Format: A mettre sur rack, Couleur du produit: Noir, Argent, Capacité du rack: 1U. Compliance certificates: RoHS, Certification: UL 1778, UL497A cULus, CE IEC 62040-2 C1-C2 / EN 55024 / CISPR22 / FCC

Caractéristiques	
capacité de la puissance de sortie *	0,55 kVA
Puissance de sortie *	420 W
Tension de voltage à l'entrée (min) *	89 V
Tension de voltage à l'entrée (max) *	151 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	100 V
Tension de voltage à la sortie (max)	125 V
Efficacité	96%
Bouton de coupure d'urgence d'alimentation (EPO)	✔
Niveau sonore	45 dB

Connectivité	
Types de sortie AC	NEMA 5–15R
Prise mâle	NEMA 5-15P
Nombre de prises en sortie	5 sortie(s) CA
Quantité de Ports USB 2.0	1
Port RS-232	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Temps de secours type au chargement complet	3 min

Batterie	
Temps de secours type à demi de charge	8 min
Batterie échangeable à chaud	✔

Design	
Format *	A mettre sur rack
Capacité du rack	1U
Longueur de câble	1,8 m
Couleur du produit *	Noir, Argent
Type d'écran	LCD
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 35 °C
Température hors fonctionnement	-15 - 40 °C
Humidité relative de fonctionnement (H-H)	0 - 90%
Altitude de fonctionnement	0 - 3000 m

Certificat	
Certificats de conformité	RoHS
Certification	UL 1778, UL497A cULus, CE IEC 62040-2 C1-C2 / EN 55024 / CISPR22 / FCC

Poids et dimensions	
Largeur	438 mm
Profondeur	364 mm
Hauteur	43,2 mm
Poids	8,95 kg

0743172043030

743172043030

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date