Eaton 5PX G2 alimentation d'énergie non interruptible Interactivité de ligne 3 kVA 3000 W 6 sortie(s) CA

Marque : Eaton

Code produit: 5PX3000RTG2

Nom du produit : 5PX G2



Eaton 5PX G2. Topologie UPS: Interactivité de ligne, capacité de la puissance de sortie: 3 kVA, Puissance de sortie: 3000 W. Types de sortie AC: NEMA L5-20R, Prise mâle: NEMA 5-20P, Nombre de prises en sortie: 6 sortie(s) CA. Temps de secours type à demi de charge: 17 min. Format: Rack/Tour, Couleur du produit: Noir, Gris, Capacité du rack: 2U. Compliance certificates: CE, REACH, Certification: CULus RoHS NOM ENERGY STAR certified BSMI IEC 62040-1



Caractéristiques	
Topologie UPS *	Interactivité de ligne
capacité de la puissance de sortie *	3 kVA
Puissance de sortie *	3000 W
Forme d'onde *	Sinusoïde pur
Tension de voltage à l'entrée (min) *	70 V
Tension de voltage à l'entrée (max) *	153 V
Fréquence d'entrée *	50/60 Hz
Estimation de montée subite d'énergie	380 J
Niveau sonore	50 dB
Protection contre les surtensions	✔
Dispositifs de protection électrique	Surcharge

Connectivité	
Types de sortie AC	NEMA L5-20R
Prise mâle	NEMA 5-20P
Nombre de prises en sortie	6 sortie(s) CA
Port USB	✔
Interface série	✔
Type d'interface série	RS-232
Nombre de ports série	1
Technologie de cablâge	10/100/1000Base-T(X)

Batterie	
Temps de secours type à demi de charge	17 min
Batterie échangeable à chaud	✔
Test de batterie automatique	✔

Design	
Format *	Rack/Tour
Capacité du rack	2U
Couleur du produit *	Noir, Gris
Type d'écran	LCD
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 50 °C
Humidité relative de fonctionnement (H-H)	20 - 90%
Taux d'humidité relative (stockage)	10 - 90%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 10000 m

Certificat	
Certificats de conformité	CE, REACH
Certification	CULus RoHS NOM ENERGY STAR certified BSMI IEC 62040-1

Contenu de l'emballage	
Kit de montage en rack	✔
Câbles inclus	RS-232, Câble USB
Carte de gestion intégrée	✔
Guide d'installation rapide	✔

Poids et dimensions	
Largeur	431,8 mm
Profondeur	601,9 mm
Hauteur	76,2 mm
Poids	33,8 kg

0743172105714

743172105714

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date