Eaton 9PX3000GLRT alimentation d'énergie non interruptible Double-conversion (en ligne) 3000 W 3 sortie(s) CA

Marque : Eaton

Code produit: 9PX3000GLRT

Nom du produit : 9PX3000GLRT

Eaton 9PX3000GLRT. Topologie UPS: Double-conversion (en ligne), Puissance de sortie: 3000 W, Tension de voltage à l'entrée (min): 100 V. Types de sortie AC: NEMA L6-20R, NEMA L6-30R, Prise mâle: NEMA L6-20P, Nombre de prises en sortie: 3 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA). Format: Rack/Tour, Couleur du produit: Noir, Argent, Capacité du rack: 2U. Compliance certificates: RoHS, Certification: IEC 62040-2 Class B Cat C2 / CISPR22 Class B / FCC part 15 Class B / VCCI Class B CE / cULus / NOM

Caractéristiques	
Topologie UPS *	Double-conversion (en ligne)
Puissance de sortie *	3000 W
Tension de voltage à l'entrée (min) *	100 V
Tension de voltage à l'entrée (max) *	276 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	200 V
Tension de voltage à la sortie (max)	240 V
Régulation de la tension de sortie	1%
Efficacité	93%
Facteur de puissance	1
Facteur de puissance d'entrée	0,99
Bouton de coupure d'urgence d'alimentation (EPO)	✔
Tension de sortie THD	3%
Niveau sonore	47 dB
Protection contre les surtensions	✔

Connectivité	
Types de sortie AC	NEMA L6-20R, NEMA L6-30R
Prise mâle	NEMA L6-20P
Nombre de prises en sortie	3 sortie(s) CA
Port USB	✔
Quantité de Ports USB 2.0	1
Interface série	✔
Type d'interface série	RS-232
Port RS-232	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Démarrage à froid	✔

Design	
Format *	Rack/Tour
Capacité du rack	2U
Couleur du produit *	Noir, Argent
Type d'écran	LCD
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 55 °C
Humidité relative de fonctionnement (H-H)	0 - 96%
Altitude de fonctionnement	0 - 3000 m

Certificat	
Certificats de conformité	RoHS
Certification	IEC 62040-2 Class B Cat C2 / CISPR22 Class B / FCC part 15 Class B / VCCI Class B CE / cULus / NOM

Contenu de l'emballage	
Câbles inclus	Cable d'éntrée, Cable de sortie, RS-232, Câble USB
Manuel d'utilisation	✔
Guide d'installation rapide	✔

Sustainability	
Certificats de durabilité	ENERGY STAR

Poids et dimensions	
Largeur	440 mm
Profondeur	605 mm
Hauteur	86,5 mm
Poids	27,4 kg

Autres caractéristiques	
Tension nominale de sortie	208 V
Tension nominale à l'entrée	208 V



0743172081315



743172081315

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date