Eaton 9PX 700RT alimentation d'énergie non interruptible Double-conversion (en ligne) 0,7 kVA 630 W 8 sortie(s) CA

Marque : Eaton

Code produit: 9PX700RT

Nom du produit : 9PX 700RT

Eaton 9PX 700RT. Topologie UPS: Double-conversion (en ligne), capacité de la puissance de sortie: 0,7 kVA, Puissance de sortie: 630 W. Types de sortie AC: NEMA 5–15R, Prise mâle: NEMA 5-15P, Nombre de prises en sortie: 8 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA). Format: Rack/Tour, Couleur du produit: Noir, Argent, Capacité du rack: 2U. Compliance certificates: RoHS, Certification: CE, cULus, NOM

Caractéristiques	
Topologie UPS *	Double-conversion (en ligne)
capacité de la puissance de sortie *	0,7 kVA
Puissance de sortie *	630 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	100 V
Tension de voltage à l'entrée (max) *	144 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	100 V
Tension de voltage à la sortie (max)	125 V
fréquence de sortie	50/60 Hz
Intensité (max.)	20 A
Temps de réponse	0 ms
Efficacité	89,9%
Tension de sortie THD	3%
Courant d'entrée THD	3%
Niveau sonore	40 dB
Protection contre les surtensions	✔
Fonctions de protection de surtensions	Réseau
Gestion basée sur le web	✔
Redémarrage automatique	✔

Connectivité	
Types de sortie AC	NEMA 5–15R
Prise mâle	NEMA 5-15P
Nombre de prises en sortie	8 sortie(s) CA
Port USB	✔
Quantité de Ports USB 2.0	1
Interface série	✔
Type d'interface série	RS-232
Port RS-232	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Batterie échangeable à chaud	✔
Démarrage à froid	✔

Design	
Format *	Rack/Tour
Capacité du rack	2U
Longueur de câble	2,44 m
Couleur du produit *	Noir, Argent
Type d'écran	LCD
Voyants	Statut

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	0 - 35 °C
Humidité relative de fonctionnement (H-H)	0 - 96%
Taux d'humidité relative (stockage)	0 - 96%
Altitude de fonctionnement	0 - 3000 m

Certificat	
Certificats de conformité	RoHS
Certification	CE, cULus, NOM

Contenu de l'emballage	
Câbles inclus	RS-232, Câble USB
Manuel d'utilisation	✔

Sustainability	
Certificats de durabilité	ENERGY STAR

Poids et dimensions	
Largeur	440 mm
Profondeur	450 mm
Hauteur	86,5 mm
Poids	16,5 kg

Informations sur l'emballage	
Support	✔
Type d'emballage	Boîte

0743172081247

743172081247

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date