StarTech.com

StarTech.com AF212C-POE-INJECTOR adaptateur et injecteur PoE 1.25 Gigabit Ethernet, 2.5 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet





Marque : StarTech.com

Code produit: AF212C-POE-INJECTOR

Nom du produit : AF212C-POE-INJECTOR

StarTech.com AF212C-POE-INJECTOR. Type d'interface Ethernet: 1.25 Gigabit Ethernet, 2.5 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet, LAN Ethernet : taux de transfert des données: 10,100,1000,2500 Mbit/s, Standards réseau: IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bz, IEEE 802.3i, IEEE 802.3u. Couleur du produit: Noir, Distance de fonctionnement maximum: 100 m, Voyants: Énergie. Tension d'entrée de l'adaptateur secteur: 100 - 240 V, Courant d'entrée: 0.8 A, Tension sortie de l'adaptateur secteur: 54 V. Compliance certificates: RoHS. Poids: 100 g

Réseau	
Type d'interface Ethernet	1.25 Gigabit Ethernet, 2.5 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet
LAN Ethernet : taux de transfert des données	10,100,1000,2500 Mbit/s
Connexion Ethernet, supportant l'alimentation via ce port (PoE)	✔
Standards réseau	IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bz, IEEE 802.3i, IEEE 802.3u
Auto MDI/MDI-X	✔
Types de câbles soutenus	Cat5, Cat5e, Cat6, Cat6a
Jeu de composants	Monolithic Power Systems - MP3924

Caractéristiques	
Couleur du produit	Noir
Protection contre les surtensions	✔
Distance de fonctionnement maximum	100 m
Voyants	Énergie
Support de trames étendues (Jumbo Frames)	✔
Trames géantes	9000
Négociation automatique	✔

Connectivité	
ports d'entrée RJ-45	1
ports de sortie RJ-45	1

Puissance	
Tension d'entrée de l'adaptateur secteur	100 - 240 V
Courant d'entrée	0.8 A
Tension sortie de l'adaptateur secteur	54 V
Courant de sortie	0,6 A

Puissance	
Consommation électrique typique	32,4 W
Port par alimentation PoE (Power over Ethernet)	30 W
Protection contre les surtensions	2 kV

Certificat	
Certificats de conformité	RoHS

Conditions environnementales	
Température d'opération	0 - 50 °C
Humidité relative de fonctionnement (H-H)	5 - 95%
Température hors fonctionnement	-10 - 70 °C

Poids et dimensions	
Poids	100 g

Contenu de l'emballage	
Cordon d'alimentation inclus	✔
Guide d'installation rapide	✔

Informations sur l'emballage	
Largeur du colis	124 mm
Profondeur du colis	210 mm
Hauteur du colis	51 mm
Poids du paquet	364 g

Données logistiques	
Largeur du carton principal	520 mm
Longueur du carton principal	285 mm
Hauteur du carton principal	455 mm
Quantité par carton principal	40 pièce(s)



0065030905787



065030905787

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date