# APC AP7869B unité de distribution d'énergie 30 sortie(s) CA 0U Noir





**Marque :** APC

**Code produit:** AP7869B

**Nom du produit :** AP7869B

APC AP7869B. Types de PDU: Avec mesure en ligne, Capacité du rack: 0U, Type: Triphasé. Nombre de prises en sortie: 30 sortie(s) CA, Types de sortie AC: Coupleur C13, Coupleur C19, NEMA L6-30R, Prise mâle: CS8365. Longueur de câble: 0,91 m, Produits compatibles: FCC Part 15 class A ICES-003 UL 60950. Tension nominale à l'entrée: 208 V, Intensité (max.): 50 A, Fréquence d'entrée AC: 50 - 60 Hz. Largeur: 56 mm, Profondeur: 95 mm, Hauteur: 1778 mm

| Design | |
|---|---|
| Types de PDU * | Avec mesure en ligne |
| Type | Triphasé |
| Capacité du rack * | 0U |
| Montage | horizontale/verticale |
| Couleur du produit | Noir |

| Connectivité | |
|---|---|
| Nombre de prises en sortie * | 30 sortie(s) CA |
| Prise mâle | CS8365 |
| Types de sortie AC * | Coupleur C13, Coupleur C19, NEMA L6-30R |

| Caractéristiques | |
|---|---|
| Longueur de câble | 0,91 m |
| Produits compatibles | FCC Part 15 class A ICES-003 UL 60950 |

| Puissance | |
|---|---|
| Tension nominale à l'entrée * | 208 V |
| Fréquence d'entrée AC | 50 - 60 Hz |
| Intensité (max.) * | 50 A |
| Tension nominale de sortie | 208 V |
| Capacité d'alimentation/charge | 14400 VA |
| Nombre de phases | 3 |
| Puissance max. | 14400 W |

| Conditions environnementales | |
|---|---|
| Température d'opération | -5 - 45 °C |

| Conditions environnementales | |
|---|---|
| Température hors fonctionnement | -25 - 65 °C |
| Humidité relative de fonctionnement (H-H) | 5 - 95% |
| Taux d'humidité relative (stockage) | 5 - 95% |
| Altitude de fonctionnement | 0 - 3048 m |
| Température d'opération | 23 - 113 °F |

| Poids et dimensions | |
|---|---|
| Largeur | 56 mm |
| Profondeur | 95 mm |
| Hauteur | 1778 mm |
| Poids | 10,4 kg |

| Contenu de l'emballage | |
|---|---|
| Manuel d'utilisation | ✔ |
| Contenu de l'emballage | Cord retention bracket(s) Documentation CD Installation guide Rack Mounting brackets RS-232 configuration cable Toolless Mounting Kit |

| Informations sur l'emballage | |
|---|---|
| Poids du paquet | 14,3 kg |
| Largeur du colis | 79 mm |
| Profondeur du colis | 311 mm |
| Hauteur du colis | 2057 mm |



0731304331544



731304331544

**Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date