APC AP7921B unité de distribution d'énergie 8 sortie(s) CA 0U/1U Noir





Marque : APC

Code produit: AP7921B

Nom du produit : Netshelter - Bandeau de prises commutées rackable - 1U 16A 208-230V - 8xC13

Netshelter - Bandeau de prises commutées rackable - 1U 16A 208-230V - 8xC13
APC AP7921B. Types de PDU: Avec mesure en ligne, Commutable, Capacité du rack: 0U/1U, Montage: horizontale/verticale. Nombre de prises en sortie: 8 sortie(s) CA, Types de sortie AC: Coupleur C13, Prise mâle: Coupleur C20. Longueur de câble: 2,5 m. Surveillance: Courant, Énergie, Tension, Contrôle de sortie: Verrouiller, Recycler, Allumer, Eteindre. Tension nominale à l'entrée: 200-230 V, Intensité (max.): 16 A, Fréquence d'entrée AC: 50 - 60 Hz

Design	
Types de PDU *	Avec mesure en ligne, Commutable
Capacité du rack *	0U/1U
Montage	horizontale/verticale
Couleur du produit	Noir

Connectivité	
Nombre de prises en sortie *	8 sortie(s) CA
Prise mâle	Coupleur C20
Types de sortie AC *	Coupleur C13
Type de connexion d'entrée	IEC-320 C20

Caractéristiques	
Longueur de câble	2,5 m

Caractéristiques de gestion	
Surveillance	Courant, Énergie, Tension
Contrôle de sortie	Verrouiller, Recycler, Allumer, Eteindre

Puissance	
Tension nominale à l'entrée *	200-230 V
Fréquence d'entrée AC	50 - 60 Hz
Intensité (max.) *	16 A
Tension nominale de sortie	208-230 V
Capacité d'alimentation/charge	3680 VA
Courant d'entrée maximum par phase	16 A
Utilisation maximale de courant par phase	16 A
Puissance max.	3680 W

Certificat	
Certificats de conformité	RoHS
Certification	cUL Listed, CE, CSA, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, GOST, IRAM, MIC, UL 60950, UL Listed, VDE, VCCI, REACH

Conditions environnementales	
Température d'opération	0 - 45 °C
Température hors fonctionnement	-25 - 65 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	1 - 15000 m

Poids et dimensions	
Largeur	445 mm
Profondeur	108 mm
Hauteur	44 mm
Poids	2,27 kg

Informations sur l'emballage	
Poids du paquet	3,45 kg
Largeur du colis	470 mm
Profondeur du colis	343 mm
Hauteur du colis	70 mm

Données logistiques	
Empreinte carbone totale (kg of CO2e)	915,89



0731304331629



731304331629

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date