APC AP7968B unité de distribution d'énergie 24 sortie(s) CA 0U Noir



Marque : APC

Code produit: AP7968B

Nom du produit : APC - Rack pduswitchedzerou12.5 kw208v(21) - Professionnels

APC - Rack pduswitchedzerou12.5 kw208v(21) - Professionnels
APC AP7968B. Types de PDU: Avec contrôle en ligne, Commutable, Capacité du rack: 0U, Montage: verticale. Nombre de prises en sortie: 24 sortie(s) CA, Types de sortie AC: Coupleur C13, Coupleur C19, Type de connexion d'entrée: CS8365. Longueur de câble: 0,91 m. Surveillance: Courant, Contrôle de sortie: Recycler, Allumer, Mise à niveau du microprogrammable via: Réseau. Tension nominale à l'entrée: 208 V, Intensité (max.): 35 A, Fréquence d'entrée AC: 50 - 60 Hz

Design	
Types de PDU *	Avec contrôle en ligne, Commutable
Capacité du rack *	0U
Montage	verticale
Couleur du produit	Noir

Connectivité	
Nombre de prises en sortie *	24 sortie(s) CA
Types de sortie AC *	Coupleur C13, Coupleur C19
Type de connexion d'entrée	CS8365

Caractéristiques	
Longueur de câble	0,91 m

Caractéristiques de gestion	
Surveillance	Courant
Contrôle de sortie	Recycler, Allumer
Micrologiciel évolutif	✔
Mise à niveau du microprogrammable via	Réseau

Puissance	
Tension nominale à l'entrée *	208 V
Fréquence d'entrée AC	50 - 60 Hz
Intensité (max.) *	35 A
Tension nominale de sortie	208 V
Capacité d'alimentation/charge	12500 VA
Utilisation maximale de courant par phase	35 A
Dispositifs de protection électrique	Surcharge

Certificat	
Certificats de conformité	RoHS
Certification	cUL, CSA, FCC Part 15 Class A, ICES-003, UL 60950, UL, REACH

Conditions environnementales	
Température d'opération	-5 - 45 °C
Température hors fonctionnement	-25 - 65 °C
Humidité relative de fonctionnement (H-H)	5 - 95%
Taux d'humidité relative (stockage)	5 - 95%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 15000 m

Poids et dimensions	
Largeur	56 mm
Profondeur	89 mm
Hauteur	1778 mm
Poids	8,08 kg

Contenu de l'emballage	
Contenu de l'emballage	Cord Retention Bracket(s), Documentation CD, Installation Guide, Rack Mounting Brackets, RS-232 configuration cable, Toolless Mounting Kit

Informations sur l'emballage	
Poids du paquet	11 kg
Largeur du colis	152 mm
Profondeur du colis	127 mm
Hauteur du colis	2108 mm

0731304331650

731304331650

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date