APC AP8459WW unité de distribution d'énergie 24 sortie(s) CA 0U Noir



Marque : APC

Code produit: AP8459WW

Nom du produit : APC NetShelter - Metered-by-Outlet Rack PDU - 2G - Compteur - 16A - 100 à 240V

APC NetShelter - Metered-by-Outlet Rack PDU - 2G - Compteur - 16A - 100 à 240V

APC AP8459WW unité de distribution d'énergie 24 sortie(s) CA 0U Noir:

Ce bandeau de prise en rack avec compteur d'APC fournit une alimentation sur prise individuelle qui permet une optimisation de l'énergie et une protection des circuits. Il peut recevoir une intensité maximale de 16A et une tension admissible de 100-240V. Son port pour capteur de température/humidité, ses fonctions de verrouillage et ses disjoncteurs compacts facilitent la surveillance des alimentations. Le produit repond aux normes EN 55022 class A, EN 55024, EN 61000-3-2 et EN 61000-3-3, RoHS UE et REACh.

Design	
Types de PDU *	Avec mesure en ligne, Mesuré par prise
Capacité du rack *	0U
Montage	verticale
Couleur du produit	Noir
Connectivité	
Nombre de prises en sortie *	24 sortie(s) CA
Types de sortie AC *	Coupleur C13, Coupleur C19
Caractéristiques	
Voyants	✔
Caractéristiques de gestion	
Surveillance	Courant, Énergie, Tension
Puissance	
Tension nominale à l'entrée *	200-230 V
Fréquence d'entrée AC	50 - 60 Hz
Intensité (max.) *	20 A
Tension nominale de sortie	200-230 V
Capacité d'alimentation/charge	3680 VA
Courant d'entrée maximum par phase	16 A
Utilisation maximale de courant par phase	16 A
Puissance max.	3680 W
Certificat	
Certificats de conformité	RoHS

Certificat	
Certification	EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Class A, ICES-003, PSE, UL Listed, VCCI Class A, VDE
Conditions environnementales	
Température d'opération	-5 - 45 °C
Température hors fonctionnement	-25 - 65 °C
Humidité relative de fonctionnement (H-H)	5 - 95%
Taux d'humidité relative (stockage)	5 - 95%
Altitude de non fonctionnement	0 - 15000 m
Poids et dimensions	
Largeur	56 mm
Profondeur	51 mm
Hauteur	1829 mm
Poids	5,08 kg
Informations sur l'emballage	
Poids du paquet	8,35 kg
Largeur du colis	163 mm
Profondeur du colis	117 mm
Hauteur du colis	2037 mm
Données logistiques	
Empreinte carbone totale (kg of CO2e)	4728,07

0731304317586

731304317586

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date