APC AP8865 unité de distribution d'énergie 44 sortie(s) CA 0U Noir



Marque : APC

Code produit: AP8865

Nom du produit : AP8865

APC AP8865. Types de PDU: Avec mesure en ligne, Avec contrôle en ligne, Capacité du rack: 0U, Montage: verticale. Nombre de prises en sortie: 44 sortie(s) CA, Types de sortie AC: NEMA 5-20R, Coupleur C13, Coupleur C19, Prise mâle: NEMA L21-30P. Longueur de câble: 1,82 m, Algorithme de sécurité soutenu: SNMP. Surveillance: Énergie, Tension, Énergie. Tension nominale à l'entrée: 208 V, Intensité (max.): 30 A, Fréquence d'entrée AC: 50 - 60 Hz

Design	
Types de PDU *	Avec mesure en ligne, Avec contrôle en ligne
Capacité du rack *	0U
Montage	verticale
Couleur du produit	Noir
Écran	LCD

Connectivité	
Nombre de prises en sortie *	44 sortie(s) CA
Prise mâle	NEMA L21-30P
Types de sortie AC *	NEMA 5-20R, Coupleur C13, Coupleur C19
Connexions de sortie	36x IEC 320 C13 6x IEC 320 C19 2x NEMA 5-20R

Caractéristiques	
Longueur de câble	1,82 m
Algorithme de sécurité soutenu	SNMP

Caractéristiques de gestion	
Surveillance	Énergie, Tension, Énergie

Puissance	
Tension nominale à l'entrée *	208 V
Fréquence d'entrée AC	50 - 60 Hz
Intensité (max.) *	30 A
Tension nominale de sortie	208 V
Capacité d'alimentation/charge	8600 VA
Courant d'entrée maximum par phase	30 A
Utilisation maximale de courant par phase	30 A

Certificat	
Certification	CSA C22.2 No. 60950,UL 60950-1

Conditions environnementales	
Température d'opération	5 - 60 °C
Température hors fonctionnement	-25 - 65 °C
Humidité relative de fonctionnement (H-H)	5 - 95%
Taux d'humidité relative (stockage)	5 - 95%
Altitude de non fonctionnement	0 - 15240 m

Poids et dimensions	
Largeur	56 mm
Profondeur	46 mm
Hauteur	1791 mm
Poids	7,56 kg

Contenu de l'emballage	
Manuel d'utilisation	✔

Informations sur l'emballage	
Poids du paquet	9,2 kg
Largeur du colis	107 mm
Profondeur du colis	162 mm
Hauteur du colis	200 mm

Données logistiques	
Empreinte carbone totale (kg of CO2e)	6416

7313042770644

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date