APC AP8881 unité de distribution d'énergie 42 sortie(s) CA 0U Noir



Marque : APC

Code produit: AP8881

Nom du produit : APC NetShelter - Metered Rack PDU 2G - Mesuré - 16A - 11kW - 400V triphasé

APC NetShelter - Metered Rack PDU 2G - Mesuré - 16A - 11kW - 400V triphasé

APC AP8881 unité de distribution d'énergie 42 sortie(s) CA 0U Noir:



Ce bandeau de prises rackables APC fournit une alimentation électrique fiable et sécurisée à vos équipements informatiques. Il délivre une puissance maximale de 11000 VA et peut recevoir une tension de 400 V 3 phases et une intensité maximale de 16 A. Le produit est certifié VDE et est conforme aux normes CEI 60950, CSA C22.2 No 60950, UL 60950-1, REACh et RoHS UE.
APC AP8881. Types de PDU: Avec mesure en ligne, Capacité du rack: 0U, Montage: verticale. Nombre de prises en sortie: 42 sortie(s) CA, Types de sortie AC: Coupleur C13, Coupleur C19, Prise mâle: IEC309. Longueur de câble: 1,83 m. Surveillance: Courant, Énergie, Tension. Tension nominale à l'entrée: 400 V, Intensité (max.): 16 A, Fréquence d'entrée AC: 50 - 60 Hz

Design	
Types de PDU *	Avec mesure en ligne
Capacité du rack *	0U
Montage	verticale
Couleur du produit	Noir
Connectivité	
Nombre de prises en sortie *	42 sortie(s) CA
Prise mâle	IEC309
Types de sortie AC *	Coupleur C13, Coupleur C19
Type de connexion d'entrée	IEC 309 16A 3P+N+PE, IEC 309 20A 3P+N+E
Connexions de sortie	36x IEC 320 C13 6x IEC 320 C19
Caractéristiques	
Longueur de câble	1,83 m
Caractéristiques de gestion	
Surveillance	Courant, Énergie, Tension
Puissance	
Tension nominale à l'entrée *	400 V
Fréquence d'entrée AC	50 - 60 Hz
Intensité (max.) *	16 A
Tension nominale de sortie	230 V
Capacité d'alimentation/charge	11040 VA

Puissance	
Courant d'entrée maximum par phase	16 A
Utilisation maximale de courant par phase	16 A
Puissance max.	11000 W
Certificat	
Certification	CSA C22.2 No. 60950,IEC 60950,UL 60950-1,VDE RoHS, REACH
Conditions environnementales	
Température d'opération	5 - 45 °C
Température hors fonctionnement	-25 - 65 °C
Humidité relative de fonctionnement (H-H)	5 - 95%
Taux d'humidité relative (stockage)	5 - 95%
Poids et dimensions	
Largeur	56 mm
Profondeur	44 mm
Hauteur	1791 mm
Poids	6,38 kg
Données logistiques	
Empreinte carbone totale (kg of CO2e)	41106,13



0731304277071



731304277071

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date