# APC Basic Rack PDU AP9572 unité de distribution d'énergie 15 sortie(s) CA 0U Noir



**Marque :** APC

**Code produit:** AP9572

**Nom du produit :** APC NetShelter - Basic Rack PDU - 16A - 200 à 230V - 3,3kW - 0U - (15) C13

APC NetShelter - Basic Rack PDU - 16A - 200 à 230V - 3,3kW - 0U - (15) C13

APC Basic Rack PDU AP9572 unité de distribution d'énergie 15 sortie(s) CA 0U Noir:

Ce bandeau de prises basique APC est utilisé pour alimenter en électricité les équipements installés dans une armoire de serveur ou un rack. Il est conçu pour recevoir une tension de 200 à 230V et une intensité maximale de 16A. Le produit est certifié cUL, CE, UL et VDE. Il est conforme à la directive RoHS de l'UE, garantissant qu'il est exempt de substances dangereuses.
APC Basic Rack PDU AP9572. Types de PDU: Basique, Capacité du rack: 0U, Montage: verticale. Nombre de prises en sortie: 15 sortie(s) CA, Types de sortie AC: Coupleur C13, Prise mâle: Coupleur C20. Longueur de câble: 2,5 m. Tension nominale à l'entrée: 23 V, Tension de sortie: 230 V, Capacité d'alimentation/charge: 3680 VA. Largeur: 44 mm, Profondeur: 44 mm, Hauteur: 620 mm

| Design | |
|---|---|
| Types de PDU * | Basique |
| Capacité du rack * | 0U |
| Montage | verticale |
| Couleur du produit | Noir |

| Connectivité | |
|---|---|
| Nombre de prises en sortie * | 15 sortie(s) CA |
| Prise mâle | Coupleur C20 |
| Types de sortie AC * | Coupleur C13 |
| Type de connexion d'entrée | IEC-320 C20 |
| Connexions de sortie | (15) IEC 320 C13 |

| Caractéristiques | |
|---|---|
| Longueur de câble | 2,5 m |

| Puissance | |
|---|---|
| Tension nominale à l'entrée * | 23 V |
| Tension de sortie | 230 V |
| Capacité d'alimentation/charge | 3680 VA |

| Puissance | |
|---|---|
| Courant d'entrée maximum par phase | 16 A |
| Utilisation maximale de courant par phase | 16 A |
| Puissance max. | 3680 W |

| Conditions environnementales | |
|---|---|
| Température d'opération | 0 - 45 °C |
| Température hors fonctionnement | -25 - 65 °C |
| Humidité relative de fonctionnement (H-H) | 5 - 95% |
| Taux d'humidité relative (stockage) | 5 - 95% |

| Poids et dimensions | |
|---|---|
| Largeur | 44 mm |
| Profondeur | 44 mm |
| Hauteur | 620 mm |
| Poids | 2 kg |



0731304226369



731304226369

**Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date