APC APDU10450ME unité de distribution d'énergie 48 sortie(s) CA 0U Noir



Marque : APC

Code produit: APDU10450ME

Nom du produit : APDU10450ME

APC APDU10450ME. Types de PDU: Commutable, Capacité du rack: 0U, Type: Monophasé. Nombre de prises en sortie: 48 sortie(s) CA, Types de sortie AC: Coupleur C13, Coupleur C15, Coupleur C19, Coupleur C21, Prise mâle: IEC 60309. Tension nominale à l'entrée: 415 V, Intensité (max.): 60 A, Fréquence d'entrée AC: 50 - 60 Hz. Certification: CSA C22.2 No 62368-1, FCC part 15 subpart B, UL 62368-1. Largeur: 56 mm, Profondeur: 75 mm, Hauteur: 1826 mm

Design	
Types de PDU *	Commutable
Type	Monophasé
Capacité du rack *	0U
Montage	verticale
Couleur du produit	Noir
Écran	LCD
Bouton marche/arrêt intégré	✗

Connectivité	
Nombre de prises en sortie *	48 sortie(s) CA
Prise mâle	IEC 60309
Types de sortie AC *	Coupleur C13, Coupleur C15, Coupleur C19, Coupleur C21

Caractéristiques	
Connexion en guirlande	✓

Puissance	
Tension nominale à l'entrée *	415 V
Fréquence d'entrée AC	50 - 60 Hz
Intensité (max.) *	60 A
Tension nominale de sortie	240 V
Tension de sortie	240 V
Capacité d'alimentation/charge	34600 VA
Courant d'entrée maximum par phase	60 A
Utilisation maximale de courant par phase	48 A

Certificat	
Certification	CSA C22.2 No 62368-1, FCC part 15 subpart B, UL 62368-1

Conditions environnementales	
Température d'opération	-5 - 60 °C
Température hors fonctionnement	-25 - 65 °C
Humidité relative de fonctionnement (H-H)	5 - 95%
Taux d'humidité relative (stockage)	5 - 95%
Altitude de fonctionnement	0 - 3048 m
Altitude de non fonctionnement	0 - 15240 m

Poids et dimensions	
Largeur	56 mm
Profondeur	75 mm
Hauteur	1826 mm
Poids	11,7 kg

Informations sur l'emballage	
Poids du paquet	14,7 kg
Largeur du colis	262 mm
Profondeur du colis	132 mm
Hauteur du colis	1980 mm

Données logistiques	
Empreinte carbone totale (kg of CO2e)	21687,02



0731304439103



731304439103

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date