APC BE850G2 alimentation d'énergie non interruptible Veille 0,85 kVA 450 W 9 sortie(s) CA



Marque : APC

Code produit: BE850G2

Nom du produit : BE850G2

APC BE850G2. Topologie UPS: Veille, capacité de la puissance de sortie: 0,85 kVA, Puissance de sortie: 450 W. Types de sortie AC: NEMA 5–15R, Nombre de prises en sortie: 9 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Capacité de la batterie: 104 Ah, Durée de vie totale de la batterie (max): 5 année(s). Couleur du produit: Noir, Longueur de câble: 1,52 m. Certification: California (CEC) Battery Charger, CSA C22.2 NO. 107.3, cTUVus, FCC Part 15 Class B, UL 1778



Caractéristiques	
Topologie UPS *	Veille
capacité de la puissance de sortie *	0,85 kVA
Puissance de sortie *	450 W
Tension de voltage à l'entrée (min) *	92 V
Tension de voltage à l'entrée (max) *	139 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	120 V
Tension de voltage à la sortie (max)	120 V
Estimation de montée subite d'énergie	354 J
Temps de réponse	6 ms
Niveau sonore	45 dB
Protection contre les surtensions	✔

Connectivité	
Types de sortie AC	NEMA 5–15R
Nombre de prises en sortie	9 sortie(s) CA
Port USB	✔
Quantité de Ports USB 2.0	2

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Capacité de la batterie	104 Ah
Durée de vie totale de la batterie (max)	5 année(s)

Batterie	
Temps de rechargement de la batterie	8 h

Design	
Longueur de câble	1,52 m
Couleur du produit *	Noir

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	10 - 90%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 15000 m

Certificat	
Certification	California (CEC) Battery Charger, CSA C22.2 NO. 107.3, cTUVus, FCC Part 15 Class B, UL 1778

Poids et dimensions	
Largeur	327 mm
Profondeur	105 mm
Hauteur	139 mm
Poids	4,1 kg

Informations sur l'emballage	
Largeur du colis	416 mm
Profondeur du colis	168 mm
Hauteur du colis	196 mm
Poids du paquet	4,4 kg

0731304413592

731304413592

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date