HP Engage Flex Système pour point de vente Pro-C G2



Marque : HP

Famille de produit: Engage Flex

Code produit: BF6R8UT#ABA

Nom du produit : Système pour point de vente HP Engage Flex Pro-C G2

HP Engage Flex Système pour point de vente Pro-C G2. Famille de processeur: Intel® Core™ i5, Modèle de processeur: i5-13500E, Fabricant de processeur: Intel. Mémoire interne: 16 Go, Type de mémoire interne: DDR5-SDRAM, Type de support (slot): DIMM. Capacité totale de stockage: 512 Go, Supports de stockage: SSD, Capacité du Solid State Drive (SSD): 512 Go. Fabricant de l'adaptateur graphique: Intel, Adaptateur graphique: UHD Graphics 770. Standards wifi: Wi-Fi 6E (802.11ax)

Processeur	
Fabricant de processeur	Intel
Famille de processeur *	Intel® Core™ i5
Modèle de processeur *	i5-13500E
Nombre de coeurs de processeurs	14
Nombre de threads du processeur	20
Fréquence du processeur Turbo	4,6 GHz
Fréquence du processeur	2,4 GHz
Cœurs de performance	6
Cœurs efficaces	8
Fréquence Turbo maximale des Effcient-cores	3,3 GHz
Mémoire cache du processeur	24 Mo
Carte mère chipset	Intel Q670

Mémoire	
Mémoire interne *	16 Go
Type de mémoire interne	DDR5-SDRAM
Nombre de logements pour mémoire	4
Type de support (slot)	DIMM
Fréquence de la mémoire	4800 MHz

Support de stockage	
Capacité totale de stockage *	512 Go
Supports de stockage *	SSD
Capacité du Solid State Drive (SSD)	512 Go
Interface du Solid State Drive (SSD)	PCI Express
NVMe	✔
Facteur de forme SSD	M.2

Graphique	
Fabricant de l'adaptateur graphique	Intel
Adaptateur graphique	UHD Graphics 770

Réseau	
Ethernet/LAN *	✔
Bluetooth *	✔
Wifi *	✔
Standards wifi	Wi-Fi 6E (802.11ax)

Connectivité	
Nombre de port ethernet LAN (RJ-45)	1
Quantité de Ports USB 2.0	2
Quantité de ports de type A USB 3.2 Gen 1 (3.1 Gen 1)	5
Quantité d'interface DisplayPorts	1

Connecteurs d'extension	
PCI Express x1 emplacement	2

Design	
Type de châssis	SFF
Nombre de baies 2,5 "	2
Couleur du produit	Noir

Logiciel	
Système d'exploitation installé *	Windows 11 Pro

Puissance	
Alimentation d'énergie	250 W

Conditions environnementales	
Humidité relative de fonctionnement (H-H)	20 - 85%
Température d'opération	10 - 40 °C

Poids et dimensions	
Largeur	300 mm
Profondeur	302 mm
Hauteur	100 mm
Poids	3,99 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date