APC BK500BLK alimentation d'énergie non interruptible Interactivité de ligne 0,5 kVA 300 W



Marque : APC

Code produit: BK500BLK

Nom du produit : BK500BLK

APC BK500BLK. Topologie UPS: Interactivité de ligne, capacité de la puissance de sortie: 0,5 kVA, Puissance de sortie: 300 W. Technologie batterie: Plomb-Acide, Temps de secours type au chargement complet: 2,4 min, Temps de secours type à demi de charge: 13,9 min. Format: Tower, Couleur du produit: Noir, Longueur de câble: 1,8 m. Certification: FCC Part 15 Class B/Industry Canada/UL 1778/cUL. Sécurité: UL,/FCC/CE/C-Tick

Caractéristiques	
Topologie UPS *	Interactivité de ligne
capacité de la puissance de sortie *	0,5 kVA
Puissance de sortie *	300 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	98 V
Tension de voltage à l'entrée (max) *	140 V
Fréquence d'entrée *	50/60 Hz
fréquence de sortie	50/60 Hz
Estimation de montée subite d'énergie	480 J
Alarmes sonores	✔
Modes d'alarme sonore	Alarme en mode batterie, Alarme de batterie faible, Alarme de surcharge

Connectivité	
Port USB	✔

Batterie	
Technologie batterie	Plomb-Acide
Temps de secours type au chargement complet	2,4 min
Temps de secours type à demi de charge	13,9 min
Temps de rechargement de la batterie	8 h
Batterie échangeable à chaud	✔

Design	
Format *	Tower
Longueur de câble	1,8 m
Couleur du produit *	Noir
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	5 - 95%
Taux d'humidité relative (stockage)	5 - 95%
Altitude de fonctionnement	0 - 3000 m

Certificat	
Certification	FCC Part 15 Class B/Industry Canada/UL 1778/cUL

Safety regulation & standards	
Sécurité	UL,/FCC/CE/C-Tick

Poids et dimensions	
Largeur	91 mm
Profondeur	284 mm
Hauteur	165 mm
Poids	6,27 kg

Informations sur l'emballage	
Poids du paquet	6,95 kg

Données logistiques	
Quantité par palette	80 pièce(s)

Autres caractéristiques	
Connexions de sortie	6 x NEMA 5-15R
Type de connexion d'entrée	NEMA 5-15P
Dimensions (LxPxH)	91 x 284 x 165 mm
Tension nominale de sortie	120 V
Tension nominale à l'entrée	120 V
Humidité hors fonctionnement	0 - 95%
Poids (impérial)	6,26 kg (13.8 kg)
Température d'opération	0 - 40 °F
Dimensions du colis (LxPxH)	175 x 357 x 263 mm

0731304021360

731304021360

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date