APC BK500 alimentation d'énergie non interruptible 0,5 kVA 300 W



Marque : APC

Code produit: BK500

Nom du produit : BK500

Back-UPS CS 500

APC BK500 alimentation d'énergie non interruptible 0,5 kVA 300 W:

APC Back-UPS CS, 300 Watts / 500 VA,Entrée 120V / Sortie 120V, Interface Port DB-9 RS-232, USB.

Comprend: Logiciel sur cédérom, Sangles de gestion des câbles, Câble USB, Manuel utilisateur.
APC BK500. capacité de la puissance de sortie: 0,5 kVA, Puissance de sortie: 300 W, Estimation de montée subite d'énergie: 480 J. Technologie batterie: Sealed Lead Acid (VRLA), Temps de secours type au chargement complet: 2,4 min, Temps de secours type à demi de charge: 13,9 min. Couleur du produit: Beige, Longueur de câble: 1,83 m. Certification: C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE. Poids: 6,27 kg



Caractéristiques	
capacité de la puissance de sortie *	0,5 kVA
Puissance de sortie *	300 W
Estimation de montée subite d'énergie	480 J
Niveau sonore	45 dB
Alarmes sonores	✔

Connectivité	
Nombre de sorties IEC jumpers	2
Quantité de Ports USB 2.0	1
Nombre de ports série	1
Ports (RJ11) du modem	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Temps de secours type au chargement complet	2,4 min
Temps de secours type à demi de charge	13,9 min
Temps de rechargement de la batterie	6 h

Design	
Longueur de câble	1,83 m
Couleur du produit *	Beige
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m

Certificat	
Certification	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE

Poids et dimensions	
Poids	6,27 kg

Informations sur l'emballage	
Poids du paquet	6,95 kg

Données logistiques	
Quantité par palette	80 pièce(s)
Code du système harmonisé	85078000

Autres caractéristiques	
Interface	Serial, USB
Connexions de sortie	(3) NEMA 5-15R, (3) NEMA 5-15R
Type de connexion d'entrée	IEC-320-C14
Dimensions (LxPxH)	91 x 284 x 165 mm
Tension nominale de sortie	120 V
Tension nominale à l'entrée	230 V
Filtrage	✔
Dimensions du colis (LxPxH)	241 x 368 x 178 mm

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date

0731304016304

731304016304

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date