APC BX1500M alimentation d'énergie non interruptible Interactivité de ligne 1,5 kVA 900 W 10 sortie(s) CA





Marque : APC

Code produit: BX1500M

Nom du produit : BX1500M

APC BX1500M. Topologie UPS: Interactivité de ligne, capacité de la puissance de sortie: 1,5 kVA, Puissance de sortie: 900 W. Types de sortie AC: NEMA 5–15R, Nombre de prises en sortie: 10 sortie(s) CA, Technologie de cablâge: 10/100/1000Base-T(X). Technologie batterie: Sealed Lead Acid (VRLA), Temps de rechargement de la batterie: 16 h. Format: Tower, Couleur du produit: Noir, Type d'écran: LCD. Compliance certificates: RoHS, Certification: California (CEC) Battery Charger, FCC Part 15 Class B, UL 1778

Caractéristiques	
Topologie UPS *	Interactivité de ligne
capacité de la puissance de sortie *	1,5 kVA
Puissance de sortie *	900 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	88 V
Tension de voltage à l'entrée (max) *	139 V
Fréquence d'entrée *	60 Hz
Tension de voltage à la sortie (max)	120 V
Régulation de la fréquence de sortie	60 Hz
Intensité (max.)	12 A
Estimation de montée subite d'énergie	789 J
Alarmes sonores	✔
Modes d'alarme sonore	Alarme en mode batterie, Alarme de batterie faible, Alarme de surcharge

Connectivité	
Types de sortie AC	NEMA 5–15R
Nombre de prises en sortie	10 sortie(s) CA
Nombre de port ethernet LAN (RJ-45)	1
Technologie de cablâge	10/100/1000Base-T(X)

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)

Batterie	
Temps de rechargement de la batterie	16 h

Design	
Format *	Tower
Couleur du produit *	Noir
Type d'écran	LCD

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 40 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	0 - 95%

Certificat	
Certificats de conformité	RoHS
Certification	California (CEC) Battery Charger, FCC Part 15 Class B, UL 1778

Sustainability	
Certificats de durabilité	ENERGY STAR

Poids et dimensions	
Largeur	100 mm
Profondeur	382 mm
Hauteur	250 mm
Poids	11 kg

Informations sur l'emballage	
Largeur du colis	227 mm
Profondeur du colis	491 mm
Hauteur du colis	348 mm
Poids du paquet	12,7 kg



0731304331780



731304331780

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date