Epson C11CF37201 imprimante matricielle (à points) 612 caractères par seconde



Marque : Epson

Code produit: C11CF37201

Nom du produit : C11CF37201

Epson C11CF37201. Vitesse maximale d'impression: 612 caractères par seconde, Vitesse d'impression maximale (qualité brouillon): 463 caractères par seconde, Vitesse d'impression maximale (basse qualité): 115 caractères par seconde. rang d'épaisseur de feuille de coupe: 0,12 - 0,46 mm, Rang d'épaisseur de papier continu: 0,46 - 0,46 mm. Couleur du produit: Noir, Taille du buffer: 128 Ko, Sound pressure level (printing): 55 dB. Interfaces standards: Parallèle, USB 2.0. Tête d'impression: 9 broches, Durée de vie de la tête d'impression: 400 million de caractères, Durée de vie du ruban: 7,5 million de caractères

Vitesse d'impression	
Largeur d'impression maximum *	80
Couleur *	✕
Vitesse maximale d'impression *	612 caractères par seconde
Vitesse d'impression maximale (qualité brouillon)	463 caractères par seconde
Vitesse d'impression maximale (basse qualité)	115 caractères par seconde
Mesure du nombre de caractère par pouce	10 caractères par pouce
Codes barres intégrés	CODABAR (NW-7), Code 128 (A/B/C), Code 39, Industrial 2/5, Matrix 2/5, POSTNET, UPC-A, UPC-E
Table de charactères	ISO 8859-15, Italique, PC437, PC850, PC858, Roman 8

Gestion du papier	
rang d'épaisseur de feuille de coupe	0,12 - 0,46 mm
Rang d'épaisseur de papier continu	0,46 - 0,46 mm

Caractéristiques	
Couleur du produit *	Noir
Taille du buffer *	128 Ko
Niveau de pression sonore (impression) *	55 dB
Langues de la description de page *	ESC P, PPDS

Connectivité	
Interfaces standards *	Parallèle, USB 2.0

Autonomie	
Tête d'impression *	9 broches
Durée de vie de la tête d'impression	400 million de caractères
Durée de vie du ruban	7,5 million de caractères
Temps moyen entre pannes	20000 h

Puissance	
Tension d'entrée AC	120 V
Fréquence d'entrée AC	50 - 60 Hz

Conditions environnementales	
Température d'opération	5 - 35 °C
Température hors fonctionnement	-30 - 60 °C
Humidité relative de fonctionnement (H-H)	10 - 80%
Taux d'humidité relative (stockage)	30 - 60%

Poids et dimensions	
Largeur	437 mm
Profondeur	376 mm
Hauteur	177 mm
Poids	7,17 kg

Technical details	
Certificats de durabilité	ENERGY STAR

0010343938045

010343938045

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date