# StarTech.com CAT6UTP3FTWH câble de réseau Blanc 0,91 m Cat6 U/UTP (UTP) Rond



**Marque :** StarTech.com

**Code produit:** CAT6UTP3FTWH

**Nom du produit :** CAT6UTP3FTWH

StarTech.com CAT6UTP3FTWH. Longueur de câble: 0,91 m, Câble standard: Cat6, Blindage du câble: U/UTP (UTP), Connecteur 1: RJ-45, Connecteur 2: RJ-45, Contacts du connecteur de placage: Or, Taux de transfert de données: 1000 Mbit/s, Couleur du produit: Blanc



| Caractéristiques | |
|---|---|
| Couleur du produit * | Blanc |
| Longueur de câble * | 0,91 m |
| Câble standard * | Cat6 |
| Blindage du câble * | U/UTP (UTP) |
| Connecteur 1 * | RJ-45 |
| Connecteur 2 * | RJ-45 |
| Genre de connecteur 1 * | Mâle |
| Genre de connecteur 2 * | Mâle |
| Facteur de forme du connecteur 1 | Droit |
| Facteur de forme du connecteur 2 | Droit |
| Contacts du connecteur de placage | Or |
| Matériau du manteau | Polyvinyl chloride (PVC) |
| Forme du câble * | Rond |
| Type de conducteur | Gainé |
| Matériau conducteur | Cuivre |
| Type d'interface Ethernet | 10 Gigabit Ethernet |
| Standards réseau | IEEE 802.3bt |
| Taille des fils AWG | 24 |
| Taux de transfert de données | 1000 Mbit/s |
| Fréquence | 250 MHz |
| Connexion Ethernet, supportant l'alimentation via ce port (PoE) | ✔ |
| Type Power over Ethernet (PoE) pris en charge | PoE++ (4PPoE) |

| Caractéristiques | |
|---|---|
| Budget Total Power over Ethernet (PoE) | 100 W |
| Résistant au feu | ✔ |
| Câble avec protection anticoupure | ✔ |
| Plug and Play | ✔ |
| **Conditions environnementales** | |
| Température d'opération | -20 - 60 °C |
| Température hors fonctionnement | 0 - 50 °C |
| Humidité relative de fonctionnement (H-H) | 0 - 90% |
| **Certificat** | |
| Certification | TIA/EIA-T568B |
| **Poids et dimensions** | |
| Diamètre extérieur | 6 mm |
| **Contenu de l'emballage** | |
| Quantité | 1 pièce(s) |
| **Informations sur l'emballage** | |
| Largeur du colis | 15 mm |
| Profondeur du colis | 180 mm |
| Hauteur du colis | 210 mm |
| Poids du paquet | 60 g |
| **Données logistiques** | |
| Largeur du carton principal | 200 mm |
| Longueur du carton principal | 300 mm |
| Hauteur du carton principal | 460 mm |
| Quantité par carton principal | 220 pièce(s) |

0065030939065

065030939065

**Catalog Object Cloud**

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date