CyberPower CP685AVRG alimentation d'énergie non interruptible Interactivité de ligne 0,685 kVA 390 W 8 sortie(s) CA





Marque : CyberPower

Code produit: CP685AVRG

Nom du produit : CP685AVRG

CyberPower CP685AVRG. Topologie UPS: Interactivité de ligne, capacité de la puissance de sortie: 0,685 kVA, Puissance de sortie: 390 W. Prise mâle: NEMA 5-15P, Nombre de prises en sortie: 8 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Capacité de la batterie: 7 Ah, Tension des piles: 12 V. Format: Compact, Couleur du produit: Noir. Compliance certificates: RoHS

Caractéristiques	
Topologie UPS *	Interactivité de ligne
capacité de la puissance de sortie *	0,685 kVA
Puissance de sortie *	390 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	90 V
Tension de voltage à l'entrée (max) *	140 V
Fréquence d'entrée *	57/63 Hz
tension de voltage à la sortie (min)	120 V
Tension de voltage à la sortie (max)	120 V
fréquence de sortie	50/60 Hz
Régulation de la tension de sortie	5%
Régulateur de tension automatique (AVR)	✔
Estimation de montée subite d'énergie	1030 J
Temps de réponse	4 ms
Protection contre les surtensions	✔
Alarmes sonores	✔
Modes d'alarme sonore	Alarme de batterie faible, Alarme de surcharge

Connectivité	
Prise mâle	NEMA 5-15P
Nombre de prises en sortie	8 sortie(s) CA
Port USB	✔
Interface série	✔
Nombre de ports série	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Capacité de la batterie	7 Ah
Tension des piles	12 V
Nombre de cellules de batterie	1
Temps de secours type au chargement complet	2 min
Temps de secours type à demi de charge	11 min
Temps de rechargement de la batterie	8 h
Cartouche de batterie de rechange	RB1270B

Design	
Format *	Compact
Couleur du produit *	Noir
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 35 °C
Humidité relative de fonctionnement (H-H)	0 - 90%

Certificat	
Certificats de conformité	RoHS

Contenu de l'emballage	
Câbles inclus	Cable d'éntrée

Safety regulation & standards	
Sécurité	UL1778, cUL 107.3, FCC DOC Class B

Poids et dimensions	
Largeur	11 mm
Profondeur	3,5 mm
Hauteur	6,8 mm
Poids	5,3 kg

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date