CyberPower

CyberPower CP850PFCLCD alimentation d'énergie non interruptible Interactivité de ligne 0,85 kVA 510 W 10 sortie(s) CA





Marque : CyberPower

Code produit: CP850PFCLCD

Nom du produit : CP850PFCLCD

CyberPower CP850PFCLCD. Topologie UPS: Interactivité de ligne, capacité de la puissance de sortie: 0,85 kVA, Puissance de sortie: 510 W. Types de sortie AC: NEMA 5–15R, Nombre de prises en sortie: 10 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Temps de secours type au chargement complet: 2 min, Temps de secours type à demi de charge: 10 min. Format: Tower, Couleur du produit: Noir, Longueur de câble: 1,52 m. Compliance certificates: RoHS, Certification: UL1778, cUL 107.3, FCC DOC Class B

Caractéristiques	
Topologie UPS *	Interactivité de ligne
capacité de la puissance de sortie *	0,85 kVA
Puissance de sortie *	510 W
Tension de voltage à l'entrée (min) *	78 V
Tension de voltage à l'entrée (max) *	142 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	120 V
Tension de voltage à la sortie (max)	120 V
Estimation de montée subite d'énergie	1030 J
Alarmes sonores	✔

Connectivité	
Types de sortie AC	NEMA 5–15R
Nombre de prises en sortie	10 sortie(s) CA
Nombre de ports série	1
Ports (RJ11) du modem	1
Nombre de port ethernet LAN (RJ-45)	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Temps de secours type au chargement complet	2 min
Temps de secours type à demi de charge	10 min
Temps de rechargement de la batterie	8 h
Batterie échangeable à chaud	✘

Design	
Format *	Tower
Longueur de câble	1,52 m
Couleur du produit *	Noir
Type d'écran	LCD
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 40 °C
Humidité relative de fonctionnement (H-H)	0 - 90%

Certificat	
Certificats de conformité	RoHS
Certification	UL1778, cUL 107.3, FCC DOC Class B

Autres caractéristiques	
Type de batterie	12V/8.5AH
Poids (impérial)	6,76 kg (14.9 kg)
Dimensions (L x L x H)	99,1 x 264,2 x 231,1 mm (3.9 x 10.4 x 9.1")



0649532609611



649532609611

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date