D-Link

D-Link DXS-3130-28P commutateur réseau Géré L3 10G Ethernet (100/1000/10000) Connexion Ethernet, supportant l'alimentation via ce port (PoE) Noir



Marque : D-Link

Code produit: DXS-3130-28P

Nom du produit : DXS-3130-28P

D-Link DXS-3130-28P. Type de commutateur: Géré, Banc de commutateurs: L3. Type de port Ethernet RJ-45 de commutation de base: 10G Ethernet (100/1000/10000), Quantité de ports Ethernet RJ-45 de commutation de base: 24, Quantité de Ports USB 2.0: 1, Port de console: RJ-45. Répertoire MAC: 32768 entrées, Capacité de commutation: 680 Gbit/s. Standards réseau: IEEE 802.1s, IEEE 802.3af, IEEE 802.3at. Connexion Ethernet, supportant l'alimentation via ce port (PoE)

Caractéristiques de gestion	
Type de commutateur *	Géré
Banc de commutateurs	L3

Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	24
Type de port Ethernet RJ-45 de commutation de base *	10G Ethernet (100/1000/10000)
Nombre de ports de gestion	1 pièce(s)
Port de console	RJ-45
Quantité de ports SFP28	4
Quantité de Ports USB 2.0	1

Réseau	
Standards réseau *	IEEE 802.1s, IEEE 802.3af, IEEE 802.3at
Soutien 10G *	✔
Port mirroring (Mise en miroir des ports)	✔
Assistance contrôle des flux	✔

Transmition des données	
Capacité de commutation *	680 Gbit/s
Taux de transfert	298 Mpps
Répertoire MAC *	32768 entrées
Support de trames étendues (Jumbo Frames)	✔
Mémoire cache de paquet	4 Mo

Sécurité	
Fonctions DHCP	DHCP client, DHCP server, DHCPv6 relay
Liste de contrôle d'accès (ACL)	✔
Algorithme de sécurité soutenu	SNMP

Protocoles	
Protocole de routage	OSPFv2, OSPFv3, VRRP
Fonctions IPv4 et IPv6	Dual stack IPv4/IPv6, IPv6 TFTP

Design	
Empilable *	✔
Couleur du produit	Noir

représentation / réalisation	
Temps moyen entre pannes	286,4952 h

Puissance	
Source d'alimentation *	Secteur
Bloc d'alimentation inclus *	✔
Nombre d'alimentations d'énergie	2
Tension d'entrée AC	100 - 240 V
Fréquence d'entrée AC	50/60 Hz

PoE (alimentation via le port Ethernet)	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✔

Conditions environnementales	
Température d'opération	0 - 50 °C
Température hors fonctionnement	-40 - 70 °C
Humidité relative de fonctionnement (H-H)	10 - 90%
Taux d'humidité relative (stockage)	5 - 90%
Dissipation thermique	3439,64 BTU/h

Poids et dimensions	
Largeur	440 mm
Profondeur	470 mm
Hauteur	44 mm
Poids	6,48 kg

0790069801716

790069801716

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date