TP-Link Omada EAP653 UR point d'accès réseaux locaux sans fil 2402 Mbit/s Blanc Connexion Ethernet, supportant l'alimentation via ce port (PoE)

Marque : TP-Link **Famille de produit:** Omada **Code produit:** EAP653 UR

Nom du produit : EAP653 UR

TP-Link Omada EAP653 UR. 2,4 GHz, 5 GHz, Débit de transfert des données maximum: 2402 Mbit/s. Algorithme de sécurité soutenu: WPA, WPA2, WPA3. LAN Ethernet : taux de transfert des données: 10,100,1000 Mbit/s. Connexion Ethernet, supportant l'alimentation via ce port (PoE). Couleur du produit: Blanc

Caractéristiques	
2,4 GHz *	✔
5 GHz *	✔
6 GHz *	✘
Débit de transfert des données maximum *	2402 Mbit/s
Débit de transfert des données maximum (2,4 GHz)	574 Mbit/s
Débit de transfert des données maximum (5 GHz)	2402 Mbit/s
LAN Ethernet : taux de transfert des données	10,100,1000 Mbit/s
Bande de fréquence	2.4 - 5 GHz
Standards réseau	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11h
Technologie de cablâge	10/100/1000Base-T(X)
Nombre d'utilisateurs	250 utilisateur(s)
Sélection automatique du canal	✔
Balayage de canal automatique	✔
MIMO (entrées multiples, sorties multiples)	✔
Type MIMO	Multi User MIMO
Méthode de propagation du spectre	OFDMA
Monter les fonctions du mode AP	Réseau maillé
Support VLAN	✔
Limitation du débit	✔
Assistance contrôle des flux	✔
Direction de la bande	✔
Airtime Fairness (ATF)	✔
Qualité de service (QoS)	✔
BeamForming	✔
Puissance de transmission (CE)	27 DBm
Puissance de transmission (FCC)	22 DBm

Sécurité	
Algorithme de sécurité soutenu *	WPA, WPA2, WPA3
Filtrage d'adresse MAC	✔
Caractéristiques de gestion	
Gestion basée sur le web	✔
Syslog	✔
Micrologiciel évolutif	✔
Connectivité	
Nombre de port ethernet LAN (RJ-45) *	1
Entrée DC	✔
Puissance	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✔
Gamme de tension continue	12 V
Design	
Positionnement *	Plafond, Mur
Couleur du produit *	Blanc
Bouton de réinitialisation	✔
Voyants	✔
Antenne	
Type d'antenne *	Interne
Poids et dimensions	
Largeur	160 mm
Profondeur	160 mm
Hauteur	33,6 mm
Informations sur l'emballage	
Type d'emballage	Boîte
Contenu de l'emballage	
Quantité	1 pièce(s)
Kit de montage	✔
Guide de démarrage rapide	✔
Conditions environnementales	
Humidité relative de fonctionnement (H-H)	10 - 90%
Température d'opération	0 - 40 °C
Température hors fonctionnement	-40 - 70 °C
Taux d'humidité relative (stockage)	5 - 90%

8885020620566

8885020620573

0810142820271

810142820271

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date