NETGEAR

NETGEAR GS108E-400NAS commutateur réseau Non-géré L2/L3 Gigabit Ethernet (10/100/1000) Gris





Marque : NETGEAR

Code produit: GS108E-400NAS

Nom du produit : GS108E-400NAS

NETGEAR GS108E-400NAS. Type de commutateur: Non-géré, Banc de commutateurs: L2/L3. Type de port Ethernet RJ-45 de commutation de base: Gigabit Ethernet (10/100/1000), Quantité de ports Ethernet RJ-45 de commutation de base: 8. Répertoire MAC: 4000 entrées, Capacité de commutation: 16 Gbit/s. Standards réseau: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Voltage d'entrée DC: 12 V

Caractéristiques de gestion	
Type de commutateur *	Non-géré
Banc de commutateurs	L2/L3
Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	8
Type de port Ethernet RJ-45 de commutation de base *	Gigabit Ethernet (10/100/1000)
Réseau	
Standards réseau *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x
Soutien 10G *	✗
Types de câbles soutenus	Cat5e, Cat6, Cat6+, Cat6a, Cat6e, Cat7, Cat7e, Cat8, Cat8.1
Port mirroring (Mise en miroir des ports)	✓
LAN Ethernet : taux de transfert des données	10,100,1000 Mbit/s
Support VLAN	✓
Fonctions LAN virtuelles	Port-based VLAN, Tagged VLAN
Nombre de VLANs	64
Transmition des données	
Capacité de commutation *	16 Gbit/s
Répertoire MAC *	4000 entrées
Sécurité	
Liste de contrôle d'accès (ACL)	✓
Caractéristiques de multidiffusion	
Support à la multidifusion	✓

Caractéristiques de multidiffusion	
Nombre de groupes multicast filtrés	128
Design	
Couleur du produit	Gris
Voyants	Activité, Liaison, Énergie, Vitesse, Système
représentation / réalisation	
Sans ventilateur	✓
Temps moyen entre pannes	2463431 h
Puissance	
Source d'alimentation *	CC
Bloc d'alimentation inclus *	✓
Voltage d'entrée DC	12 V
Courant d'entrée	1.5 A
Consommation (max)	3,7 W
Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-20 - 70 °C
Humidité relative de fonctionnement (H-H)	10 - 90%
Altitude de fonctionnement	0 - 3000 m
Dissipation thermique	8,9 BTU/h
Poids et dimensions	
Largeur	158 mm
Profondeur	101 mm
Hauteur	29 mm
Poids	508 g

0606449169942

606449169942

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date