NETGEAR

NETGEAR GS305E Géré Gigabit Ethernet (10/100/1000) Noir

Marque : NETGEAR

Code produit: GS305E-100NAS

Nom du produit : GS305E



NETGEAR GS305E. Type de commutateur: Géré. Type de port Ethernet RJ-45 de commutation de base: Gigabit Ethernet (10/100/1000), Quantité de ports Ethernet RJ-45 de commutation de base: 5. Répertoire MAC: 8000 entrées, Capacité de commutation: 10 Gbit/s. Standards réseau: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x



Caractéristiques de gestion	
Type de commutateur *	Géré
Qualité de service (QoS)	✔
Gestion basée sur le web	✔

Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	5
Type de port Ethernet RJ-45 de commutation de base *	Gigabit Ethernet (10/100/1000)

Réseau	
Standards réseau *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Port mirroring (Mise en miroir des ports)	✔
Assistance contrôle des flux	✔
Agrégation de lien	✘
Limitation du débit	✔
Support VLAN	✔
Fonctions LAN virtuelles	Port-based VLAN, Tagged VLAN
Nombre de VLANs	64

Transmition des données	
Capacité de commutation *	10 Gbit/s
Répertoire MAC *	8000 entrées
Enregistrement-et-réémission	✔
Support de trames étendues (Jumbo Frames)	✔
Trames géantes	9000

Sécurité	
Fonctions DHCP	DHCP client

Sécurité	
Filtrage IGMP	✔
Protection en boucle	✔
Protection par mot de passe	✔

Design	
Grille de montage *	✘
Couleur du produit	Noir
Voyants	Activité, Liaison, Énergie, Vitesse, Système

représentation / réalisation	
Temps moyen entre pannes	2531294 h

PoE (alimentation via le port Ethernet)	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✘

Conditions environnementales	
Température d'opération	0 - 50 °C
Température hors fonctionnement	-20 - 70 °C
Humidité relative de fonctionnement (H-H)	0 - 90%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 3000 m

Poids et dimensions	
Largeur	94 mm
Profondeur	100 mm
Hauteur	27 mm
Poids	250 g

0606449140521

606449140521

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date