NETGEAR

NETGEAR GS308-300PAS commutateur réseau Non-géré L2 Gigabit Ethernet (10/100/1000) Noir



Marque : NETGEAR

Code produit: GS308-300PAS

Nom du produit : GS308-300PAS

NETGEAR GS308-300PAS. Type de commutateur: Non-géré, Banc de commutateurs: L2. Type de port Ethernet RJ-45 de commutation de base: Gigabit Ethernet (10/100/1000), Quantité de ports Ethernet RJ-45 de commutation de base: 8. Répertoire MAC: 8000 entrées, Capacité de commutation: 16 Gbit/s. Standards réseau: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u. Connecteur d'alimentation: DC-in jack. Montage mural

Caractéristiques de gestion	
Type de commutateur *	Non-géré
Banc de commutateurs	L2
Qualité de service (QoS)	✔

Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	8
Type de port Ethernet RJ-45 de commutation de base *	Gigabit Ethernet (10/100/1000)
Quantité de ports .Gigabit Ethernet (copper)	8
Connecteur d'alimentation	DC-in jack

Réseau	
Standards réseau *	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u
Soutien 10G *	✘
Technologie de câblage Ethernet cuivre	10BASE-T, 100BASE-TX, 1000BASE-T
Assistance contrôle des flux	✔
Auto MDI/MDI-X	✔
Détection auto	✔
Détection de la longueur du câble	✔

Transmition des données	
Capacité de commutation *	16 Gbit/s
Taux de transfert	1,448 Mpps
Répertoire MAC *	8000 entrées
Latence (1 Gbps)	2,6 µs
Support de trames étendues (Jumbo Frames)	✔
Trames géantes	9216

Transmition des données	
Mémoire cache de paquet	128 Mo

Design	
Grille de montage *	✘
Couleur du produit	Noir
Matériau du boîtier/corps	Métal
Voyants	Activité, Liaison, Énergie
Montage mural	✔

représentation / réalisation	
Temps moyen entre pannes	3711898 h

Puissance	
Consommation (max)	3,04 W

PoE (alimentation via le port Ethernet)	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✘

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-20 - 70 °C
Humidité relative de fonctionnement (H-H)	0 - 90%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Dissipation thermique	10,4 BTU/h

Poids et dimensions	
Largeur	158 mm
Profondeur	101 mm
Hauteur	29 mm
Poids	390 g

0606449140132

606449140132

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date