NETGEAR

NETGEAR 8-Port Gig Plus Switch Géré L2/L3 Gigabit Ethernet (10/100/1000) Noir





Marque : NETGEAR

Code produit: GS308E-400NAS

Nom du produit : 8-Port Gig Plus Switch

NETGEAR 8-Port Gig Plus Switch. Type de commutateur: Géré, Banc de commutateurs: L2/L3. Type de port Ethernet RJ-45 de commutation de base: Gigabit Ethernet (10/100/1000), Quantité de ports Ethernet RJ-45 de commutation de base: 8. Full duplex. Répertoire MAC: 4000 entrées, Capacité de commutation: 16 Gbit/s. Standards réseau: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3at, IEEE 802.3af. Voltage d'entrée DC: 12 V

Caractéristiques de gestion	
Type de commutateur *	Géré
Banc de commutateurs	L2/L3
Qualité de service (QoS)	✔
Gestion basée sur le web	✔
Support MIB	✔

Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	8
Type de port Ethernet RJ-45 de commutation de base *	Gigabit Ethernet (10/100/1000)

Réseau	
Standards réseau *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3at, IEEE 802.3af
Soutien 10G *	✘
Port mirroring (Mise en miroir des ports)	✔
Full duplex	✔
Assistance contrôle des flux	✔
Agrégation de lien	✔
Contrôle Broadcast storm	✔
LAN Ethernet : taux de transfert des données	1000 Mbit/s
Support VLAN	✔

Transmition des données	
Capacité de commutation *	16 Gbit/s
Répertoire MAC *	4000 entrées
Support de trames étendues (Jumbo Frames)	✔
Trames géantes	9216

Sécurité	
Fonctions DHCP	DHCP client
Filtrage IGMP	✔
Protection en boucle	✔

Caractéristiques de multidiffusion	
Support à la multidifusion	✔

Design	
Couleur du produit	Noir
Voyants	✔

Puissance	
Source d'alimentation *	CC
Bloc d'alimentation inclus *	✔
Voltage d'entrée DC	12 V
Courant d'entrée	1.5 A
Tension d'entrée	12 V

PoE (alimentation via le port Ethernet)	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✘

Autres caractéristiques	
Période de garantie	5 année(s)

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-20 - 70 °C
Humidité relative de fonctionnement (H-H)	0 - 90%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m

Poids et dimensions	
Largeur	158 mm
Profondeur	101 mm
Hauteur	29 mm
Poids	500 g

Contenu de l'emballage	
Câbles inclus	Secteur



0606449170054



606449170054

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date