NETGEAR

NETGEAR GS324 Non-géré Gigabit Ethernet (10/100/1000) 1U Noir

Marque : NETGEAR

Code produit: GS324-200NAS

Nom du produit : GS324



NETGEAR GS324. Type de commutateur: Non-géré. Type de port Ethernet RJ-45 de commutation de base: Gigabit Ethernet (10/100/1000), Quantité de ports Ethernet RJ-45 de commutation de base: 24. Répertoire MAC: 8000 entrées, Capacité de commutation: 48 Gbit/s. Standards réseau: IEEE 802.3, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.1p, IEEE 802.3az. Montage mural, Grille de montage, Format: 1U



Caractéristiques de gestion	
Type de commutateur *	Non-géré
Qualité de service (QoS)	✔

Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	24
Type de port Ethernet RJ-45 de commutation de base *	Gigabit Ethernet (10/100/1000)

Réseau	
Standards réseau *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.1p, IEEE 802.3az
Soutien 10G *	✘
Types de câbles soutenus	Cat5
Auto MDI/MDI-X	✔
Détection auto	✔

Transmition des données	
Capacité de commutation *	48 Gbit/s
Répertoire MAC *	8000 entrées
Latence (1 Gbps)	4,7 µs
Support de trames étendues (Jumbo Frames)	✔
Trames géantes	9216
Taux de transfert des paquets (1 Gbps)	1448000 pps
Mémoire cache de paquet	0,512 Mo

Design	
Grille de montage *	✔
Format	1U
Couleur du produit	Noir
Voyants	Activité, Liaison, Énergie, Vitesse
Montage mural	✔

représentation / réalisation	
Sans ventilateur	✔
Temps moyen entre pannes	1016877 h

Puissance	
Source d'alimentation *	Secteur
Bloc d'alimentation inclus *	✔
Tension d'entrée AC	100 - 240 V
Fréquence d'entrée AC	50/60 Hz
Courant d'entrée	0.7 A
Consommation électrique typique	4,33 W
Consommation (max)	12,1 W

PoE (alimentation via le port Ethernet)	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✘

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-20 - 70 °C
Humidité relative de fonctionnement (H-H)	0 - 90%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Dissipation thermique	41,2 BTU/h

Poids et dimensions	
Largeur	252 mm
Profondeur	180 mm
Hauteur	44 mm
Poids	1,21 kg

Contenu de l'emballage	
Câbles inclus	Secteur
Manuel d'utilisation	✔

Certificat	
Certification	CE Mark, FCC 15 A, IC A, RCM, CCC, VCCI, KC, CB, CE LVD

0606449151459

606449151459

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date