NETGEAR

NETGEAR GS516UP Non-géré Gigabit Ethernet (10/100/1000) Connexion Ethernet, supportant l'alimentation via ce port (PoE) Gris



Marque : NETGEAR

Code produit: GS516UP-100NAS

Nom du produit : GS516UP

NETGEAR GS516UP. Type de commutateur: Non-géré. Type de port Ethernet RJ-45 de commutation de base: Gigabit Ethernet (10/100/1000), Quantité de ports Ethernet RJ-45 de commutation de base: 16. Full duplex. Répertoire MAC: 8000 entrées, Capacité de commutation: 32 Gbit/s. Standards réseau: IEEE 802.3ae, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3p, IEEE 802.3u. Connexion Ethernet, supportant l'alimentation via ce port (PoE). Grille de montage



Caractéristiques de gestion	
Type de commutateur *	Non-géré
Qualité de service (QoS)	✔

Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	16
Type de port Ethernet RJ-45 de commutation de base *	Gigabit Ethernet (10/100/1000)

Réseau	
Standards réseau *	IEEE 802.3ae, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3p, IEEE 802.3u
Soutien 10G *	✘
Full duplex	✔
Semi-duplex	✔
Auto MDI/MDI-X	✔

Transmition des données	
Capacité de commutation *	32 Gbit/s
Répertoire MAC *	8000 entrées
Support de trames étendues (Jumbo Frames)	✔
Taux de transfert des paquets (1 Gbps)	1448000 pps

Design	
Grille de montage *	✔
Couleur du produit	Gris
Matériau du boîtier/corps	Métal
Voyants	Activité, Liaison, PoE, Énergie, Vitesse
Nombre de ventilateurs	3 ventilateur(s)

représentation / réalisation	
Temps moyen entre pannes	1213791 h

Puissance	
Source d'alimentation *	PoE
Tension d'entrée AC	100 - 240 V
Fréquence d'entrée AC	50/60 Hz
Courant d'entrée	8 - 4 A
Consommation (max)	456,8 W

PoE (alimentation via le port Ethernet)	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✔
Quantité de ports Power Over Ethernet plus (PoE+)	16
Port par alimentation PoE (Power over Ethernet)	60 W
Budget Total Power over Ethernet (PoE)	380 W

Conditions environnementales	
Température d'opération	0 - 50 °C
Température hors fonctionnement	-20 - 70 °C
Humidité relative de fonctionnement (H-H)	10 - 90%
Altitude de fonctionnement	0 - 3000 m
Dissipation thermique	1559,5152 BTU/h

Poids et dimensions	
Largeur	390 mm
Profondeur	220 mm
Hauteur	43 mm
Poids	2,6 kg

0606449149739

606449149739

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date