NETGEAR

NETGEAR GSM4328 Géré L3 Gigabit Ethernet (10/100/1000) Connexion Ethernet, supportant l'alimentation via ce port (PoE) 1U Noir



Marque : NETGEAR

Code produit: GSM4328-100NES

Nom du produit : GSM4328

NETGEAR GSM4328. Type de commutateur: Géré, Banc de commutateurs: L3. Type de port Ethernet RJ-45 de commutation de base: Gigabit Ethernet (10/100/1000), Quantité de ports Ethernet RJ-45 de commutation de base: 24, Nombre de modules SFP+ installés: 4. Répertoire MAC: 16000 entrées, Capacité de commutation: 128 Gbit/s. Standards réseau: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE.... Connexion Ethernet, supportant l'alimentation via ce port (PoE). Grille de montage, Format: 1U



Caractéristiques de gestion	
Type de commutateur *	Géré
Banc de commutateurs	L3
Qualité de service (QoS)	✔
Gestion basée sur le web	✔
Gestion du trafic	✔

Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	24
Type de port Ethernet RJ-45 de commutation de base *	Gigabit Ethernet (10/100/1000)
Nombre de modules SFP+ installés *	4

Réseau	
Standards réseau *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x
Soutien 10G *	✔
Support VLAN	✔
Nombre de VLANs	4093

Transmition des données	
Capacité de commutation *	128 Gbit/s
Débit	95,23 Mpps
Répertoire MAC *	16000 entrées
Mémoire cache de paquet	16 Mo

Sécurité	
Fonctions DHCP	DHCP server, DHCP snooping, DHCPv6 snooping

Design	
Grille de montage *	✔

Design	
Empilable *	✔
Format	1U
Couleur du produit	Noir

représentation / réalisation	
Niveau sonore	52 dB

Puissance	
Source d'alimentation *	Secteur
Bloc d'alimentation inclus *	✔

PoE (alimentation via le port Ethernet)	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✔
Quantité de ports Power Over Ethernet plus (PoE+)	24
Port par alimentation PoE (Power over Ethernet)	30 W
Budget Total Power over Ethernet (PoE)	648 W

Conditions environnementales	
Température d'opération	0 - 45 °C
Température hors fonctionnement	-20 - 70 °C

Poids et dimensions	
Largeur	440 mm
Profondeur	400 mm
Hauteur	43,2 mm
Poids	6,41 kg

0606449161922

606449161922

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date