StarTech.com HDMI2-CABLE-4K60-35F câble HDMI 10,6 m HDMI Type A (Standard) Noir





Marque : StarTech.com

Code produit: HDMI2-CABLE-4K60-35F

Nom du produit : HDMI2-CABLE-4K60-35F

StarTech.com HDMI2-CABLE-4K60-35F. Longueur de câble: 10,6 m, Connecteur 1: HDMI Type A (Standard), Genre de connecteur 1: Mâle, Connecteur 2: HDMI Type A (Standard), Genre de connecteur 2: Mâle, Contacts du connecteur de placage: Or, Version HDMI: 2.0, Taux de transfert des données: 18 Gbit/s, Canal de retour audio (ARC, Audio Return Channel), Couleur du produit: Noir

Caractéristiques	
Longueur de câble *	10,6 m
Connecteur 1 *	HDMI Type A (Standard)
Connecteur 2 *	HDMI Type A (Standard)
Genre de connecteur 1 *	Mâle
Genre de connecteur 2 *	Mâle
Facteur de forme du connecteur 1	Droit
Facteur de forme du connecteur 2	Droit
Couleur du produit *	Noir
Version HDMI	2.0
Résolutions graphiques prises en charge	3840 x 2160, 2560 x 1400, 1920 x 1080 (HD 1080)
Modes vidéo pris en charge	1080p, 1440p, 2160p
Canal de retour audio (ARC, Audio Return Channel)	✔
Canal Ethernet HDMI	✔
HDCP	✔
Version HDCP	2.2
Taux de transfert des données	18 Gbit/s
Prise en charge HDR	✔
Technologie HDR (plage dynamique élevée)	High Dynamic Range 10 (HDR10)
Canaux audio numérique pris en charge (non compressés)	32
Taux de d'actualisation maximal	240 Hz
Taille des fils AWG	24

Caractéristiques	
Contacts du connecteur de placage *	Or
Type de câble	Câble rond
Matériau de la prise du câble	Élastomère thermoplastique (TPE)
Blindage du câble	Plaque d'aluminium mylar
Profondeur de couleurs	12 bit
Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-20 - 70 °C
Humidité relative de fonctionnement (H-H)	10 - 90%
Certificat	
Certificats de conformité	RoHS
Poids et dimensions	
Diamètre du câble	9 mm
Poids	800 g
Informations sur l'emballage	
Largeur du colis	348 mm
Profondeur du colis	254 mm
Hauteur du colis	55 mm
Poids du paquet	800 g
Quantité *	1 pièce(s)
Données logistiques	
Largeur du carton principal	416 mm
Longueur du carton principal	312 mm
Hauteur du carton principal	313 mm
Quantité par carton principal	8 pièce(s)



0065030910620



065030910620

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date