Eaton 9155 alimentation d'énergie non interruptible 15 kVA 13500 W



Marque : Eaton

Code produit: K41512000000000

Nom du produit : 9155

Eaton 9155. capacité de la puissance de sortie: 15 kVA, Puissance de sortie: 13500 W, Tension de voltage à l'entrée (min): 200 V. Technologie batterie: Sealed Lead Acid (VRLA), Temps de secours type au chargement complet: 13 min, Temps de secours type à demi de charge: 35 min. Format: Tower, Couleur du produit: Noir, Type d'écran: LCD. Certification: IEC 62040-2, FCC Part 15, ICES-003, VCCI ISO 9001: 2000, ISO 14001:1996 UL, cUL, CSA, CE, NOM-NYCE. Sécurité: NOM-0190SCFI-1993, UL 1778, CSA C22.2, No. 107.3; EN 5502 Class A, IEC 60950, IEC 62040-1-1

Caractéristiques	
capacité de la puissance de sortie *	15 kVA
Puissance de sortie *	13500 W
Tension de voltage à l'entrée (min) *	200 V
Tension de voltage à l'entrée (max) *	240 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	100 V
Tension de voltage à la sortie (max)	220 V
Temps de réponse	1 ms
Efficacité	91%
Facteur de puissance	0,99
Courant d'entrée THD	5%
Niveau sonore	53 dB
Alarmes sonores	✔

Connectivité	
Port RS-232	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Nombre de cellules de batterie	64
Temps de secours type au chargement complet	13 min
Temps de secours type à demi de charge	35 min

Batterie	
Temps de rechargement de la batterie	3 h

Design	
Format *	Tower
Couleur du produit *	Noir
Type d'écran	LCD
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 25 °C
Altitude de fonctionnement	0 - 1000 m

Certificat	
Certification	IEC 62040-2, FCC Part 15, ICES-003, VCCI ISO 9001: 2000, ISO 14001:1996 UL, cUL, CSA, CE, NOM-NYCE

Safety regulation & standards	
Sécurité	NOM-0190SCFI-1993, UL 1778, CSA C22.2, No. 107.3; EN 5502 Class A, IEC 60950, IEC 62040-1-1

Poids et dimensions	
Largeur	304,8 mm
Profondeur	856 mm
Hauteur	1214,1 mm
Poids	267,6 kg

Autres caractéristiques	
Type de batterie	9Ah
Tension nominale de sortie	208 V
Humidité relative	0 - 95%
Protection contre les surcharges	✔

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date