ATEN KN1108VA commutateur écran, clavier et souris Grille de montage Noir



Marque : ATEN

Code produit: KN1108VA

Nom du produit : KN1108VA

Commutateur KVM sur IP Cat 5, 8 ports, accès 1 local/1 distants, avec support virtuel (1920 x 1200) ATEN KN1108VA. Port clavier: USB, PS/2, Port souris: USB, PS/2, Port vidéo: VGA. Technologie de cablâge: 10/100/1000Base-T(X), Standards réseau: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, Algorithme de sécurité soutenu: 802.1x RADIUS, FIPS 140-2, RSA, SSL/TLS. Type HD: Full HD, Résolution maximale: 1920 x 1200 pixels, Intervalle de scan: 1,255 s. Couleur du produit: Noir, Capacité du rack: 1U, Matériau du boîtier/corps: Métal. Source d'alimentation: Secteur, Tension d'entrée: 100 - 240 V, Fréquence d'entrée AC: 50 / 60 Hz



Connectivité	
Nombre d'ordinateurs contrôlés *	8
Port clavier *	USB, PS/2
Port souris *	USB, PS/2
Port vidéo *	VGA
Ports de console *	Casque de 3,5 mm, 3.5mm mic, PS/2, USB A, USB B, VGA (D-Sub)
Connecteur USB	Mini-USB B, USB Type-A
Type de port série	RJ-45
Nombre de ports série	2
Connexions audio	✔

Réseau	
Ethernet/LAN	✔
Nombre de port ethernet LAN (RJ-45)	2
Technologie de cablâge	10/100/1000Base-T(X)
Standards réseau	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
Algorithme de sécurité soutenu	802.1x RADIUS, FIPS 140-2, RSA, SSL/TLS

représentation / réalisation	
Type HD *	Full HD
Résolution maximale *	1920 x 1200 pixels
Intervalle de scan	1,255 s
Nombre d'utilisateurs	64 utilisateur(s)
Micrologiciel évolutif	✔

Design	
Grille de montage *	✔
Capacité du rack	1U
Couleur du produit *	Noir
Matériau du boîtier/corps	Métal
Commutateur distant filaire	✔
Mise en cascade possible	✔
Voyants	✔

Design	
Bouton poussez	✔
Touches directes	✔

Écran	
Écran integré *	✘

Puissance	
Source d'alimentation	Secteur
Tension d'entrée	100 - 240 V
Fréquence d'entrée AC	50 / 60 Hz
Courant d'entrée	1 A

Configuration minimale du système	
Prise en charge du système d'exploitation Windows	✔
Prise en charge du système d'exploitation Linux	✔
Prise en charge du système d'exploitation Mac	✔

Sustainability	
Certificats de conformité	RoHS

Conditions environnementales	
Température d'opération	0 - 50 °C
Température hors fonctionnement	-20 - 60 °C
Humidité relative de fonctionnement (H-H)	0 - 80%

Poids et dimensions	
Largeur	438,4 mm
Profondeur	287,8 mm
Hauteur	44 mm
Poids	3,52 kg

Contenu de l'emballage	
Câbles inclus	Secteur
Manuel d'utilisation	✔
Kit de montage en rack	✔

0672792403873

672792403873

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date