StarTech.com MCM110ST2 convertisseur de support réseau 100 Mbit/s 1310 nm



Marque : StarTech.com

Code produit: MCM110ST2

Nom du produit : MCM110ST2

StarTech.com MCM110ST2. Débit de transfert des données maximum: 100 Mbit/s, Convertisseur d'interface d'entrée: 10Base-T, 100BASE-FX, 100Base-TX, Standards réseau: IEEE 802.3, IEEE 802.3u. Distance de transfert maximale: 2000 m, Longueur d'onde: 1310 nm, Sensibilité: -31 dBmW. Matériau du boîtier/corps: Plastique. Connecteur de fibre optique: ST, Technologie de connectivité: Avec fil. Tension d'entrée: 100 - 240 V, Tension de sortie: 12 V, Courant de sortie: 0,2 A



Réseau	
Débit de transfert des données maximum *	100 Mbit/s
Convertisseur d'interface d'entrée	10Base-T, 100BASE-FX, 100Base-TX
Standards réseau	IEEE 802.3, IEEE 802.3u
LAN Ethernet : taux de transfert des données	10,100 Mbit/s
Taux de transfert de données	100 Mbit/s
Système recto-verso	Complète, Demi

représentation / réalisation	
Distance de transfert maximale *	2000 m
Longueur d'onde *	1310 nm
Multiplexage en longueur d'onde	✗
Sensibilité	-31 dBmW
Bilan de liaison	11 dB
Temps moyen entre pannes	65000 h

Caractéristiques	
Interne *	✗
Voyants	✓
Matériau du boîtier/corps	Plastique

Connectivité	
Technologie de connectivité	Avec fil
Nombre de port ethernet LAN (RJ-45)	1
Connecteur de fibre optique *	ST

Puissance	
Tension d'entrée	100 - 240 V

Puissance	
Tension de sortie	12 V
Courant de sortie	0,2 A
Consommation électrique typique	2,4 W
Connexion Ethernet, supportant l'alimentation via ce port (PoE)	✗
Type de prise	Type M

Poids et dimensions	
Largeur	75 mm
Profondeur	95 mm
Hauteur	20 mm
Poids	82 g

Conditions environnementales	
Température d'opération	0 - 50 °C
Température hors fonctionnement	-10 - 70 °C
Humidité relative de fonctionnement (H-H)	10 - 90%

Contenu de l'emballage	
Adaptateur secteur fourni	✓
Manuel d'utilisation	✓

Informations sur l'emballage	
Largeur du colis	145 mm
Profondeur du colis	175 mm
Hauteur du colis	61 mm
Poids du paquet	273 g

Certificat	
Certificats de conformité	RoHS
Certification	CE, FCC, TAA, REACH

0065030835633

065030835633

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date