NETGEAR

NETGEAR MS305-100NAS commutateur réseau Non-géré 2.5G Ethernet (100/1000/2500) Noir

Marque : NETGEAR

Code produit: MS305-100NAS

Nom du produit : MS305-100NAS



NETGEAR MS305-100NAS. Type de commutateur: Non-géré. Type de port Ethernet RJ-45 de commutation de base: 2.5G Ethernet (100/1000/2500), Quantité de ports Ethernet RJ-45 de commutation de base: 5. Full duplex, Standards réseau: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3x. Voltage d'entrée DC: 12 V. Montage mural



Caractéristiques de gestion	
Type de commutateur *	Non-géré
Qualité de service (QoS)	✔

Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	5
Type de port Ethernet RJ-45 de commutation de base *	2.5G Ethernet (100/1000/2500)

Réseau	
Standards réseau *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3x
Full duplex	✔
Semi-duplex	✔
Auto MDI/MDI-X	✔
Fonction HOL contre la saturation des en-têtes de file	✔
LAN Ethernet : taux de transfert des données	100,1000,2500 Mbit/s
Détection de la longueur du câble	✔

Transmition des données	
Latence (1 Gbps)	2458 µs
Support de trames étendues (Jumbo Frames)	✔
Trames géantes	9720
Mémoire cache de paquet	1 Mo

Design	
Grille de montage *	✘
Empilable *	✘
Couleur du produit	Noir
Matériau du boîtier/corps	Métal
Voyants	✔
Montage mural	✔
Nombre de ventilateurs	0 ventilateur(s)

représentation / réalisation	
Niveau sonore	0 dB
Sans ventilateur	✔
Temps moyen entre pannes	1401743 h

Puissance	
Source d'alimentation *	CC
Bloc d'alimentation inclus *	✔
Voltage d'entrée DC	12 V
Courant d'entrée	1 A
Tension d'entrée	12 V
Consommation électrique typique	4,6 W
Consommation (max)	9,24 W

PoE (alimentation via le port Ethernet)	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✘

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-20 - 70 °C
Humidité relative de fonctionnement (H-H)	0 - 90%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m

Poids et dimensions	
Largeur	158 mm
Profondeur	101 mm
Hauteur	29 mm
Poids	480 g

Certificat	
Certificats de conformité	CCC, Directive basse tension (DBT)

0606449160130

606449160130

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date