NETGEAR

NETGEAR MS308E 2.5G Ethernet (100/1000/2500) 1U Noir

Marque : NETGEAR

Code produit: MS308E-100NAS

Nom du produit : MS308E



NETGEAR MS308E. Type de port Ethernet RJ-45 de commutation de base: 2.5G Ethernet (100/1000/2500), Quantité de ports Ethernet RJ-45 de commutation de base: 8. Full duplex. Répertoire MAC: 16000 entrées, Capacité de commutation: 40 Gbit/s. Standards réseau: IEEE 802.1p, IEEE 802.3az, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3bz. Voltage d'entrée DC: 12 V. Montage mural, Format: 1U



Caractéristiques de gestion	
Qualité de service (QoS)	✔

Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	8
Type de port Ethernet RJ-45 de commutation de base *	2.5G Ethernet (100/1000/2500)

Réseau	
Standards réseau *	IEEE 802.1p, IEEE 802.3az, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3bz
Soutien 10G *	✘
Full duplex	✔
Semi-duplex	✔
Auto MDI/MDI-X	✔
Fonction HOL contre la saturation des en-têtes de file	✔
LAN Ethernet : taux de transfert des données	100,1000,2500 Mbit/s
Détection de la longueur du câble	✔

Transmition des données	
Capacité de commutation *	40 Gbit/s
Taux de transfert	3,72 Mpps
Répertoire MAC *	16000 entrées
Latence (1 Gbps)	4,9 µs
Support de trames étendues (Jumbo Frames)	✔
Trames géantes	12288

Design	
Grille de montage *	✘
Empilable *	✘
Format	1U
Couleur du produit	Noir
Matériau du boîtier/corps	Métal

Design	
Montage mural	✔
Nombre de ventilateurs	0 ventilateur(s)

représentation / réalisation	
Niveau sonore	0 dB
Sans ventilateur	✔
Temps moyen entre pannes	3309911 h

Puissance	
Source d'alimentation *	CC
Bloc d'alimentation inclus *	✔
Voltage d'entrée DC	12 V
Courant d'entrée	1 A
Tension d'entrée	12 V

PoE (alimentation via le port Ethernet)	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✘

Autres caractéristiques	
Période de garantie	5 année(s)

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-20 - 70 °C
Humidité relative de fonctionnement (H-H)	0 - 90%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Dissipation thermique	8,27 BTU/h

Poids et dimensions	
Largeur	158 mm
Profondeur	101 mm
Hauteur	27 mm
Poids	430 g

0606449170665

606449170665

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date