CyberPower

CyberPower OR1500PFCLCD alimentation d'énergie non interruptible Interactivité de ligne 1,5 kVA 1050 W 8 sortie(s) CA





Marque : CyberPower

Code produit: OR1500PFCLCD

Nom du produit : OR1500PFCLCD

CyberPower OR1500PFCLCD. Topologie UPS: Interactivité de ligne, capacité de la puissance de sortie: 1,5 kVA, Puissance de sortie: 1050 W. Types de sortie AC: NEMA 5–15R, Prise mâle: NEMA 5-15P, Nombre de prises en sortie: 8 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Temps de secours type au chargement complet: 4 min, Temps de secours type à demi de charge: 12 min. Format: Mini Tower, Couleur du produit: Noir, Longueur de câble: 1,8 m. Compliance certificates: RoHS

Caractéristiques	
Topologie UPS *	Interactivité de ligne
capacité de la puissance de sortie *	1,5 kVA
Puissance de sortie *	1050 W
Tension de voltage à l'entrée (min) *	78 V
Tension de voltage à l'entrée (max) *	142 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	120 V
Tension de voltage à la sortie (max)	120 V
Régulateur de tension automatique (AVR)	✔
Estimation de montée subite d'énergie	1030 J
Filtre de bruit EMI/RFI	✔
Protection contre les surtensions	✔
Dispositifs de protection électrique	Surcharge

Connectivité	
Types de sortie AC	NEMA 5–15R
Prise mâle	NEMA 5-15P
Nombre de prises en sortie	8 sortie(s) CA
Quantité de Ports USB 2.0	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)

Batterie	
Nombre de batteries prises en charge	2
Temps de secours type au chargement complet	4 min
Temps de secours type à demi de charge	12 min
Temps de rechargement de la batterie	8 h

Design	
Format *	Mini Tower
Longueur de câble	1,8 m
Couleur du produit *	Noir

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 90%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 15000 m

Certificat	
Certificats de conformité	RoHS

Safety regulation & standards	
Sécurité	UL1778 4th, cUL 107.3-05, FCC/DoC Class B

Sustainability	
Certificats de durabilité	ENERGY STAR

Poids et dimensions	
Largeur	137 mm
Profondeur	163 mm
Hauteur	351 mm
Poids	11,3 kg



0649532611997



649532611997

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date